

**Modlink MSDD-set: Frame 4000-68123-0000000,**  
insert 4000-68000-0050000 + 4000-68000-1200000

### [Link to Product](#)

#### Illustration



Product may differ from Image

<b>Frame</b>	
suitable for mounting with wall thickness	1...5 mm
Protection	IP65
Temperature range	-10...+60 °C (storage temperature -25...+60 °C)
Housing	Zinc die-casting, with surface finishing
<b>RJ45</b>	
Operating current (UL Rating)	max. 175 mA
Locking of ports	Snap In
Connection front side	RJ45
Connection rear side	RJ45
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Specification	CAT5e, Class D, 100 MHz, (EN 50173-1)
<b>France (UTE-NF)</b>	
Connection	Screw terminals: max. 2× 6 mm <sup>2</sup> (AWG 10)
Operating current	16 A
LED display	yellow
No. of poles	2 + PE
Operating voltage	250 V AC
<b>Shielding plate</b>	
Tightening torque	0.9 Nm ±0.1
Connection	Threaded hole M4
<b>Commercial data</b>	
country of origin	DE
customs tariff number	85366990
EAN	4048879466844
eClass	27189217
Packaging unit	1.000