

### Product type designation

### C-PLUG

C-PLUG, replaceable medium for simple device exchange in case of failure, for storage of configuration or user data and application data applicable in SIMATIC NET products with C-Plug slot



### Permitted ambient conditions

|                                                                |                |
|----------------------------------------------------------------|----------------|
| Ambient temperature                                            |                |
| • during operation                                             | 0 ... 60 °C    |
| • during storage                                               | -40 ... +80 °C |
| • during transport                                             | -40 ... +80 °C |
| Relative humidity                                              |                |
| • at 25 °C / without condensation / during operation / maximum | 95 %           |
| Protection class IP                                            | IP20           |

### Design, dimensions and weight

|                                 |         |
|---------------------------------|---------|
| Width                           | 24.3 mm |
| Height                          | 17 mm   |
| Depth                           | 8.1 mm  |
| Net weight                      | 5 g     |
| design of the removable storage |         |
| • C-PLUG                        | Yes     |
| • KEY-PLUG                      | No      |

## Product properties, functions, components / general

|                  |           |
|------------------|-----------|
| Storage capacity | 32 Mibyte |
|------------------|-----------|

## Further Information / Internet Links

### Internet-Link

- |                                                      |                                                                                                     |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| • to website: TIA Selection Tool                     | <a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>   |
| • to website: Selector SIMATIC NET<br>SELECTION TOOL | <a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>                               |
| • to the website: IWLAN                              | <a href="http://www.siemens.com/iwlan">http://www.siemens.com/iwlan</a>                             |
| • to website: Industrial communication               | <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>                 |
| • to website: Industry Mall                          | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                   |
| • to website: Information and Download Center        | <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> |
| • to website: Image database                         | <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>             |
| • to website: CAx Download Manager                   | <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                 |
| • to website: Industry Online Support                | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>             |

**last modified:**

10/12/2016