

WITHDRAWABLE CIRCUIT BREAKER WITHOUT GUIDE FRAME 3-POLE, SIZE II, IEC IN=3200A TO 690V, AC50/60HZ ICU=80KA AT 500V REAR CONNECTION HORIZONTAL

Model		
product brandname		SENTRON
Product designation		ACB
Design of the operating mechanism		Pushbutton
Type of the driving mechanism		Manual/motorized operating mechanism with mechanical and electrical closing
Type of the driving mechanism / motor drive		Yes
Design of the overcurrent release		ETU25B

General technical data		
Number of poles		3
Size of the circuit-breaker		2
Electrical endurance (switching cycles) / typical		15 000
Usage category		B
circuit-breaker / Design		3WL1232
Mechanical service life (switching cycles) / typical		15 000

Voltage		
Rated insulation voltage U_i	V	1 000
Insulation voltage / rated value	V	1 000

Protection class		
Protection class IP		IP20
Protective function of the overcurrent release		LSI

Dissipation		
Power loss [W]		
<ul style="list-style-type: none"> for rated value of the current / at AC / in hot operating state / per pole 	W	236.7
<ul style="list-style-type: none"> maximum 	W	710

Electricity		
Continuous current / rated value	A	3 200
Adjustable pick-up value current		
<ul style="list-style-type: none"> of instantaneous short-circuit trip unit / initial value 	A	50 000
<ul style="list-style-type: none"> of instantaneous short-circuit trip unit / Full-scale value 	A	50 000

Short-time current resistance (I_{cs})		
• limited to 0.5 s / rated value	kA	80
• limited to 1 s / rated value	kA	66
• limited to 2 s / rated value	kA	46
• limited to 3 s / rated value	kA	44

Main circuit

Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• at AC / at 50/60 Hz / rated value	V	690
Operating current		
• at 40 °C / rated value	A	3 200
• at 50 °C / rated value	A	3 200
• at 55 °C / rated value	A	3 200
• at 60 °C / rated value	A	3 020
• at 65 °C / rated value	A	3 020
• at 70 °C / rated value	A	2 870

Auxiliary circuit

Number of NC contacts / for auxiliary contacts		2
Number of NO contacts / for auxiliary contacts		2

Suitability

Suitability for use		Plant / motor protection
----------------------------	--	--------------------------

Product details

Product component		
• Trip indicator		Yes
• Voltage trigger		No
• undervoltage release		No
Product extension / optional / motor drive		No

Product function

Product function		
• Ground fault protection		No

Display and operation

Display version		without display
------------------------	--	-----------------

Short circuit

Operational short-circuit current breaking capacity (I_{cs})		
• at 415 V / rated value	kA	80
• at 500 V / rated value	kA	80

<ul style="list-style-type: none"> • at 690 V / rated value 	kA	75
Maximum short-circuit current breaking capacity (Icu)		
<ul style="list-style-type: none"> • at 415 V / rated value 	kA	80
<ul style="list-style-type: none"> • at 500 V / rated value 	kA	80
<ul style="list-style-type: none"> • at 690 V / rated value 	kA	75
Short-circuit current making capacity (Icm)		
<ul style="list-style-type: none"> • at 415 V / rated value 	kA	176
<ul style="list-style-type: none"> • at 500 V / rated value 	kA	176
<ul style="list-style-type: none"> • at 690 V / rated value 	kA	165

Connections

Arrangement of electrical connectors / for main current circuit		without guide frame
Type of electrical connection / for main current circuit		Blade contacts

Mechanical Design

Height	mm	411.5
Width	mm	451
Depth	mm	337
Mounting type		drawer unit

Environmental conditions

Ambient temperature		
<ul style="list-style-type: none"> • during operation / minimum 	°C	-20
<ul style="list-style-type: none"> • during operation / maximum 	°C	70
<ul style="list-style-type: none"> • during storage / minimum 	°C	-40
<ul style="list-style-type: none"> • during storage / maximum 	°C	70

Certificates

Equipment marking		
<ul style="list-style-type: none"> • acc. to DIN EN 61346-2 		Q
<ul style="list-style-type: none"> • acc. to DIN EN 81346-2 		Q

General Product Approval	Declaration of Conformity	Test Certificates
--------------------------	---------------------------	-------------------



CCC



VDE



EG-Konf.

[sonstig](#)

[spezielle Prüfbescheinigungen](#)

[n](#)

Shipping Approval



ABS



BUREAU VERITAS



GL



LRS



PRS



RMRS

other

[Umweltbestätigung](#)

[sonstig](#)

Further information

Industry Mall (Online ordering system)

https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3WL1232-3CB35-4AA2-Z_C22+K07

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/3WL1232-3CB35-4AA2-Z_C22+K07/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1232-3CB35-4AA2-Z_C22+K07

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

09/22/2016