

MAGNET COIL F. CONTACTORS 7,5KW AC 380V, 50/60HZ FOR MOTOR CONTACTORS SZ S0, SCREW TERMINAL,










General technical data:

product brand name	SIRIUS
Product designation	Magnet coil

Control circuit:

Type of voltage of the control supply voltage	AC
Power loss [V·A] of magnet coil at AC typical	7.6 V·A
Control supply voltage	
<ul style="list-style-type: none"> <li>• 1 at AC           <ul style="list-style-type: none"> <li>— at 50 Hz rated value</li> <li>— at 60 Hz rated value</li> </ul> </li> </ul>	380 V 380 V
Operating range factor control supply voltage rated value of magnet coil at AC	
<ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>	0.8 ... 1.1 0.85 ... 1.1

Certificates/ approvals:

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval			
	 EG-Konf.	<a href="#">spezielle Prüfbescheinigung</a> n	 ABS	 BUREAU VERITAS	 DNV	
Shipping Approval			other			
 GL	 LRS	 RMRS	<a href="#">Umweltbestätigung</a>	<a href="#">Bestätigungen</a>	 VDE	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RT2924-5AU21>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2924-5AU21>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2924-5AU21&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2924-5AU21&lang=en)

**last modified:**

10/07/2016