

\*\*\* SPARE PART\*\*\* SIMATIC SC,ELECTRONIC SUBMODULE 2 AI,  
4..20mA, +/-20MA

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	30 mA
Power loss	
Power loss, typ.	0.6 W
Hardware configuration	
Rack	
• required terminal block	TB 16SC
Slots	
• required slots	1; from 8
Analog inputs	
Number of analog inputs	2
permissible input current for current input (destruction limit), max.	40 mA; Permanent
Input ranges	
• Current	Yes
Input ranges (rated values), currents	
• -20 mA to +20 mA	Yes
• Input resistance (-20 mA to +20 mA)	50 Ω
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	50 Ω
Thermocouple (TC)	
Temperature compensation	
— parameterizable	No
Characteristic linearization	
• parameterizable	No
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution (incl. overrange)	+/-20 mA: 13 bits, 4 to 20 mA: 12 bits

• Resolution with overrange (bit including sign), max.	13 bit
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	55 / 65 ms
• Integration time (ms)	50 / 60 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz

<b>Smoothing of measured values</b>	
• parameterizable	Yes; parameterizable in 4 stages by means of digital filtering
• Step: None	Yes; 1 x cycle time
• Step: low	Yes; 8 x cycle time
• Step: Medium	Yes; 64 x cycle time
• Step: High	Yes; 128 x cycle time

## Encoder

<b>Connection of signal encoders</b>	
• for voltage measurement as 2-wire transducer	Yes; 4-wire transformer with external transmitter feed
• for current measurement as 2-wire transducer	Yes; with external transmitter supply
• for current measurement as 4-wire transducer	Yes

## Errors/accuracies

Linearity error (relative to input range), (+/-)	0.05 %
Temperature error (relative to input range), (+/-)	0.01 %/K
Crosstalk between the inputs, min.	50 dB; At 50/60 Hz
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.1 %

### Operational error limit in overall temperature range

• Current, relative to input range, (+/-)	1 %
---	-----

### Basic error limit (operational limit at 25 °C)

• Current, relative to input range, (+/-)	0.8 %
---	-------

### Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$ , f1 = interference frequency

• Series mode interference (peak value of interference < rated value of input range), min.	70 dB
• Common mode interference (USS < 2.5 V), min.	90 dB

## Interrupts/diagnostics/status information

Alarms	No
Diagnostic functions	No

## Potential separation

<b>Potential separation analog inputs</b>	
• between the channels	No
• between the channels and backplane bus	No; Optocoupler

- between the channels and the power supply of the electronics

No

#### Permissible potential difference

Between the inputs and MANA (UCM)

2 V DC / 2 Vpp AC

#### Isolation

Isolation tested with

1500 V AC

#### Dimensions

Width

10 mm

Height

64 mm

Depth

51 mm

#### Weights

Weight, approx.

20 g

**last modified:**

10/14/2016