

ACCESSORY / SPARE PART ROUND,  
22MM/SQUARE, 26X26MM: LED SUPER-BRIGHT  
LAMPS, BASE BA 9S BULB DIAMETER 10MM RATED  
VOLTAGE 48V AC/DC OPERATIONAL CURRENT  
MAX. 15 MA BLUE



Figure similar

General technical data:		
<b>Product designation</b>		LED lamp, super bright
<b>Type of light source</b>		LED
<b>Color of the light source</b>		blue
<b>Mounting type</b>		BA 9s
<b>Product component</b>		
• series resistor		No
• diode		No
• lamp transformer		No
• Light source		Yes
<b>Type of voltage for actuation</b>		AC/DC
<b>Operating voltage</b>		
• at AC		
— at 50 Hz rated value	V	48 ... 48
— at 60 Hz rated value	V	48 ... 48
• at DC rated value	V	48 ... 48
<b>Relative positive tolerance of the operating voltage</b>	%	10

Relative negative tolerance of the operating voltage	%	-15
Consumed current for rated value of supply voltage maximum	mA	9
Type of electrical connection		Miscellaneous
Mounting type		miscellaneous

#### Certificates/approvals

General Product Approval	Declaration of Conformity	Test Certificates	other
--------------------------	---------------------------	-------------------	-------



[spezielle Prüfbescheinigung](#)  
n

[Bestätigungen](#)

[Umweltbestätigung](#)

#### Further information

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB3901-1PC>

##### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB3901-1PC>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB3901-1PC>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB3901-1PC&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB3901-1PC&lang=en)

last modified:

10/07/2016