

circuit breaker VL630H high breaking capacity I<sub>cu</sub>=70kA, 415V AC 4-pole, line protection trip unit TM, LI I<sub>n</sub>=630A, rated current IR=500...630A, overload protection, II=3250...6500A, short-circuit protection N unprotected without auxiliary release without auxiliary/alarm switch

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	TM
General technical data	
number of poles	4
size of the circuit-breaker	3VL5
mechanical service life (switching cycles) / typical	10 000
electrical endurance (switching cycles) / typical	5 000
utilization category	A
performance class for circuit breaker	N
reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750	Q
operating frequency / maximum	60 1/s
Voltage	
Rated operational voltage U <sub>e</sub> / max.	690 V
<ul style="list-style-type: none"> <li>insulation voltage / rated value</li> <li>insulation voltage (U<sub>i</sub>) / at AC / rated value</li> </ul>	800 V
surge voltage resistance / rated value	8 kV
operating voltage	
<ul style="list-style-type: none"> <li>rated value / maximum</li> <li>for main current circuit / at AC / at 50 Hz / maximum</li> <li>for main current circuit / at AC / at 60 Hz / maximum</li> </ul>	690 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LI
Current	
operational current	
<ul style="list-style-type: none"> <li>at 40 °C / rated value</li> <li>at 45 °C / rated value</li> <li>at 50 °C / rated value</li> <li>at 55 °C / rated value</li> <li>at 60 °C / rated value</li> <li>at 65 °C / rated value</li> <li>at 70 °C / rated value</li> </ul>	630 A
continuous current / rated value	630 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current	
<ul style="list-style-type: none"> <li>of the current-dependent overload release / full-scale value</li> <li>of instantaneous short-circuit trip unit / minimum</li> <li>of instantaneous short-circuit trip unit / maximum</li> </ul>	630 A
	3 150 A
	6 300 A
Main circuit	
operating frequency	
<ul style="list-style-type: none"> <li>1 / rated value</li> <li>2 / rated value</li> </ul>	50 Hz
	60 Hz
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0

number of NC contacts / for auxiliary contacts	0
number of NO contacts / for auxiliary contacts	0
<b>Suitability</b>	
suitability for use	system protection
<b>Adjustable parameters</b>	
adjustable current response value current / of the current-dependent overload release / initial value	504 A
<b>Product details</b>	
product component	
• trip indicator	No
• auxiliary switch	No
• voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
product extension / optional / motor drive	Yes
<b>Product function</b>	
product function	
• of thermal overload trip unit	adjustable
• grounding protection	No
• for neutral conductors / short-circuit and overload proof	No
• overload protection	Yes
<b>Short circuit</b>	
breaking capacity operating short-circuit current (Ics)	
• at 240 V / rated value	75 kA
• at 415 V / rated value	70 kA
• at 500 V / rated value	30 kA
• at 690 V / rated value	10 kA
breaking capacity maximum short-circuit current (Icu)	
• at 240 V / rated value	100 kA
• at 415 V / rated value	70 kA
• at 440 V / rated value	50 kA
• at 480 V / according to NEMA / rated value	50 kA
• at 500 V / rated value	40 kA
• at 600 V / according to NEMA / rated value	30 kA
• at 690 V / rated value	20 kA
<b>Connections</b>	
arrangement of electrical connectors / for main current circuit	front side
type of connectable conductor cross-sections / for auxiliary contacts	
• solid	0.75 ... 1.5 mm <sup>2</sup>
• finely stranded / with core end processing	0,75 ... 1.0 mm <sup>2</sup>
type of electrical connection / for main current circuit	screw-type terminals
<b>Mechanical Design</b>	
height	279.5 mm
width	253.5 mm
depth	138.5 mm
fastening method	fixed mounting
<b>Environmental conditions</b>	
ambient temperature / during operation	
• minimum	0 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
<b>General Product Approval</b>	<b>EMC</b>

[Miscellaneous](#)



[Confirmation](#)

[TSE](#)



Declaration of Conformity	Test Certificates	Marine / Shipping
---------------------------	-------------------	-------------------



EG-Konf.

[Special Test Certificate](#)



ABS



BUREAU  
VERITAS



LRS



PRS

Marine / Shipping	other
-------------------	-------



RINA



RMRS



DNV-GL  
DNVGL.COM

[Confirmation](#)

[Miscellaneous](#)

[Environmental Confirmations](#)

other
-------

[Miscellaneous](#)

Further information
---------------------

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL5763-2EJ46-0AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3VL5763-2EJ46-0AA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL5763-2EJ46-0AA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5763-2EJ46-0AA0)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



