

circuit breaker VL160H high breaking capacity $I_{cu}=70\text{kA}$, 415V AC 4-pole, line protection Electronic Trip Unit TM, LI $I_n=50\text{A}$, rated current $I_r=40\dots50\text{A}$, overload prot. II=300...600A, short-circuit protection, N unprotected N unprotected without auxiliary release without auxiliary/alarm switch

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	TM
General technical data	
number of poles	4
size of the circuit-breaker	3VL2
mechanical service life (switching cycles) / typical	20 000
electrical endurance (switching cycles) / typical	10 000
utilization category	A
performance class for circuit breaker	N
reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750	Q
operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage U_e / max.	690 V
<ul style="list-style-type: none"> insulation voltage / rated value insulation voltage (U_i) / at AC / rated value 	800 V
surge voltage resistance / rated value	8 kV
operating voltage <ul style="list-style-type: none"> rated value / maximum for main current circuit / at AC / at 50 Hz / maximum for main current circuit / at AC / at 60 Hz / maximum for main current circuit / at DC / maximum 	690 V
	690 V
	690 V
	500 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LI
Current	
operational current <ul style="list-style-type: none"> at 40 °C / rated value at 45 °C / rated value at 50 °C / rated value at 55 °C / rated value at 60 °C / rated value at 65 °C / rated value at 70 °C / rated value 	50 A
	50 A
	50 A
	46.5 A
	46.5 A
	43 A
	43 A
continuous current / rated value	50 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current <ul style="list-style-type: none"> of the current-dependent overload release / full-scale value of instantaneous short-circuit trip unit / minimum of instantaneous short-circuit trip unit / maximum 	50 A
	300 A
	600 A
Main circuit	
operating frequency <ul style="list-style-type: none"> 1 / rated value 2 / rated value 	50 Hz
	60 Hz
Auxiliary circuit	

number of CO contacts / for auxiliary contacts	0
number of NC contacts / for auxiliary contacts	0
number of NO contacts / for auxiliary contacts	0
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the current-dependent overload release / initial value	40 A
Product details	
product component	
• trip indicator	No
• auxiliary switch	No
• voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
product extension / optional / motor drive	Yes
Product function	
product function	
• of thermal overload trip unit	adjustable
• grounding protection	No
• for neutral conductors / short-circuit and overload proof	No
• overload protection	Yes
Short circuit	
breaking capacity operating short-circuit current (Ics)	
• at 240 V / rated value	75 kA
• at 415 V / rated value	70 kA
• at 500 V / rated value	30 kA
• at 690 V / rated value	6 kA
breaking capacity maximum short-circuit current (Icu)	
• at 240 V / rated value	100 kA
• at 415 V / rated value	70 kA
• at 440 V / rated value	50 kA
• at 480 V / according to NEMA / rated value	50 kA
• at 500 V / rated value	40 kA
• at 600 V / according to NEMA / rated value	12 kA
• at 690 V / rated value	12 kA
Connections	
arrangement of electrical connectors / for main current circuit	front side
type of connectable conductor cross-sections / for main contacts	
• with flexible busbar	12 x 10 mm
• solid	2.5 ... 95 mm ²
• finely stranded / with core end processing	2.5 ... 50 mm ²
• stranded	2.5 ... 95 mm ²
type of connectable conductor cross-sections / for auxiliary contacts	
• solid	0.75 ... 1.5 mm ²
• finely stranded / with core end processing	0,75 ... 1.0 mm ²
type of electrical connection / for main current circuit	box terminal
Mechanical Design	
height	174.5 mm
width	139.5 mm
depth	106.5 mm
fastening method	fixed mounting
Environmental conditions	
ambient temperature / during operation	
• minimum	0 °C
• maximum	70 °C

ambient temperature / during storage

- minimum
- maximum

-40 °C
80 °C

General Product Approval



[Miscellaneous](#)

[Confirmation](#)

[TSE](#)

[KC](#)



EMC

Declaration of Conformity

Test Certificates

Marine / Shipping



C-Tick



EG-Konf.

[UK Declaration of Conformity](#)

[Special Test Certificate](#)



ABS



BUREAU
VERITAS

Marine / Shipping

other



LRS



PRS



RINA



RMRS



DNV-GL

[Miscellaneous](#)

other

[Environmental Conformations](#)

[Confirmation](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=3VL2705-2EJ43-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL2705-2EJ43-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mifb=3VL2705-2EJ43-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



