



Power semiconductor module 480 V, for 3RW55, 840 A

product designation	Power semiconductor module
design of the product	480 V, 840 A
manufacturer's article number	
• of soft starter	3RW5554-.HA.4 (3x)
Substance Prohibittance (Date)	10/21/2019

Ambient conditions

ambient temperature during storage	-40 ... +80 °C
------------------------------------	----------------

Certificates/ approvals

General Product Approval	Declaration of Conformity	Test Certificates
Confirmation  CCC	 EAC	 EG-Konf.
	UK Declaration of Conformity	Type Test Certificates/Test Report

Marine / Shipping

Marine / Shipping	other
 ABS	Confirmation
 LRS	
 PRS	
 DNV-GL	

Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5955-0SW04>
- Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5955-0SW04>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3RW5955-0SW04>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5955-0SW04&lang=en
- Characteristic: Tripping characteristics, I^t, Let-through current
<https://support.industry.siemens.com/cs/ww/en/ps/3RW5955-0SW04/char>
- Characteristic: Installation altitude
<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5955-0SW04&objecttype=14&gridview=view1>
- Simulation Tool for Soft Starters (STS)
<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

1/18/2021 

