

CONTACTOR, AC-3 45 KW/400 V, DC 24 V, 2 NO + 2 NC, 3-POLE,
SIZE S3, SCREW CONNECTION



| | |
|---|----------------------------|
| product brand name | SIRIUS |
| Product designation | power contactor |
| General technical data | |
| Size of contactor | S3 |
| Insulation voltage | |
| • rated value | 1 000 V |
| Degree of pollution | 3 |
| Surge voltage resistance rated value | 6 kV |
| maximum permissible voltage for safe isolation | |
| • between coil and main contacts acc. to EN 60947-1 | 690 V |
| Protection class IP | |
| • on the front | IP00 |
| • of the terminal | IP00 |
| Shock resistance | |
| • at rectangular impulse | |
| — at DC | 6,8g / 5 ms, 4g / 10 ms |
| • with sine pulse | |
| — at DC | 10,6g / 5 ms, 6,2g / 10 ms |

| | |
|---|--------------------------------|
| Mechanical service life (switching cycles) | |
| <ul style="list-style-type: none"> • of contactor typical | 10 000 000 |
| <ul style="list-style-type: none"> • of the contactor with added electronics-compatible auxiliary switch block typical | 5 000 000 |
| <ul style="list-style-type: none"> • of the contactor with added auxiliary switch block typical | 10 000 000 |
| Ambient conditions | |
| Installation altitude at height above sea level maximum | 2 000 m |
| Ambient temperature | |
| <ul style="list-style-type: none"> • during operation | -25 ... +60 °C |
| <ul style="list-style-type: none"> • during storage | -55 ... +80 °C |
| Main circuit | |
| Number of poles for main current circuit | 3 |
| Number of NO contacts for main contacts | 3 |
| Number of NC contacts for main contacts | 0 |
| Operating current | |
| <ul style="list-style-type: none"> • at AC-1 at 400 V <ul style="list-style-type: none"> — at ambient temperature 40 °C rated value | 120 A |
| <ul style="list-style-type: none"> • at AC-1 <ul style="list-style-type: none"> — up to 690 V at ambient temperature 40 °C rated value — up to 690 V at ambient temperature 60 °C rated value — up to 1000 V at ambient temperature 40 °C rated value — up to 1000 V at ambient temperature 60 °C rated value | 120 A 100 A 70 A 60 A |
| <ul style="list-style-type: none"> • at AC-3 <ul style="list-style-type: none"> — at 400 V rated value — at 690 V rated value — at 1000 V rated value | 95 A 58 A 30 A |
| Connectable conductor cross-section in main circuit at AC-1 | |
| <ul style="list-style-type: none"> • at 60 °C minimum permissible | 35 mm ² |
| <ul style="list-style-type: none"> • at 40 °C minimum permissible | 50 mm ² |
| Operating current for approx. 200000 operating cycles at AC-4 | |
| <ul style="list-style-type: none"> • at 400 V rated value | 42 A |
| <ul style="list-style-type: none"> • at 690 V rated value | 27 A |
| Operating current | |
| <ul style="list-style-type: none"> • at 1 current path at DC-1 <ul style="list-style-type: none"> — at 24 V rated value | 100 A |

| | |
|---|--|
| <ul style="list-style-type: none"> — at 110 V rated value | 9 A |
| <ul style="list-style-type: none"> • with 2 current paths in series at DC-1 <ul style="list-style-type: none"> — at 24 V rated value — at 110 V rated value | 100 A 100 A |
| <ul style="list-style-type: none"> • with 3 current paths in series at DC-1 <ul style="list-style-type: none"> — at 24 V rated value — at 110 V rated value | 100 A 100 A |
| Operating current | |
| <ul style="list-style-type: none"> • at 1 current path at DC-3 at DC-5 <ul style="list-style-type: none"> — at 24 V rated value — at 110 V rated value | 40 A 2.5 A |
| <ul style="list-style-type: none"> • with 2 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> — at 110 V rated value — at 24 V rated value | 100 A 100 A |
| <ul style="list-style-type: none"> • with 3 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> — at 110 V rated value — at 24 V rated value | 100 A 100 A |
| Operating power | |
| <ul style="list-style-type: none"> • at AC-1 <ul style="list-style-type: none"> — at 230 V at 60 °C rated value — at 400 V rated value — at 690 V rated value — at 690 V at 60 °C rated value — at 1000 V at 60 °C rated value | 38 kW 66 kW 114 kW 114 kW 98 W |
| <ul style="list-style-type: none"> • at AC-2 at 400 V rated value | 45 kW |
| <ul style="list-style-type: none"> • at AC-3 <ul style="list-style-type: none"> — at 230 V rated value — at 400 V rated value — at 500 V rated value — at 690 V rated value — at 1000 V rated value | 22 kW 45 kW 55 kW 55 kW 37 W |
| Operating power for approx. 200000 operating cycles at AC-4 | |
| <ul style="list-style-type: none"> • at 400 V rated value • at 690 V rated value | 22 kW 25.4 kW |
| Thermal short-time current limited to 10 s | 760 A |
| Power loss [W] at AC-3 at 400 V for rated value of the operating current per conductor | 10.8 W |
| No-load switching frequency | |
| <ul style="list-style-type: none"> • at DC | 1 000 1/h |
| Operating frequency | |
| <ul style="list-style-type: none"> • at AC-1 maximum | 900 1/h |

| | |
|-------------------|---------|
| • at AC-2 maximum | 350 1/h |
| • at AC-3 maximum | 850 1/h |
| • at AC-4 maximum | 250 1/h |

Control circuit/ Control

| | |
|---|---------------|
| Type of voltage of the control supply voltage | DC |
| Control supply voltage at DC | |
| • rated value | 24 V |
| Operating range factor control supply voltage rated value of magnet coil at DC | 0.8 ... 1.1 |
| Closing power of magnet coil at DC | 15 W |
| Holding power of magnet coil at DC | 15 W |
| Closing delay | |
| • at DC | 90 ... 230 ms |
| Opening delay | |
| • at DC | 14 ... 20 ms |
| Arcing time | 10 ... 15 ms |

Auxiliary circuit

| | |
|--|---|
| Number of NC contacts | |
| • for auxiliary contacts | |
| — instantaneous contact | 2 |
| Number of NO contacts | |
| • for auxiliary contacts | |
| — instantaneous contact | 2 |
| Operating current at AC-12 maximum | 10 A |
| Operating current at AC-15 | |
| • at 230 V rated value | 6 A |
| • at 400 V rated value | 3 A |
| Operating current at DC-12 | |
| • at 60 V rated value | 6 A |
| • at 110 V rated value | 3 A |
| • at 220 V rated value | 1 A |
| Operating current at DC-13 | |
| • at 24 V rated value | 10 A |
| • at 60 V rated value | 2 A |
| • at 110 V rated value | 1 A |
| • at 220 V rated value | 0.3 A |
| Contact reliability of auxiliary contacts | 1 faulty switching per 100 million (17 V, 1 mA) |

UL/CSA ratings

| | |
|---|-------------|
| Contact rating of auxiliary contacts according to UL | A600 / Q600 |
|---|-------------|

Short-circuit protection

| | |
|--------------------------------|--|
| Design of the fuse link | |
|--------------------------------|--|

- for short-circuit protection of the main circuit
 - with type of coordination 1 required
 - with type of assignment 2 required
- for short-circuit protection of the auxiliary switch required

fuse gL/gG: 250 A
 fuse gL/gG: 160 A
 fuse gL/gG: 10 A

Installation/ mounting/ dimensions

| | |
|---|--|
| Mounting type | screw and snap-on mounting onto 35 mm and 75 mm standard mounting rail |
| <ul style="list-style-type: none"> • Side-by-side mounting | Yes |
| Height | 146 mm |
| Width | 70 mm |
| Depth | 201 mm |
| Required spacing | |
| <ul style="list-style-type: none"> • for grounded parts <ul style="list-style-type: none"> — at the side | 6 mm |

Connections/Terminals

| | |
|--|---|
| Type of electrical connection | |
| <ul style="list-style-type: none"> • for main current circuit • for auxiliary and control current circuit | <p>screw-type terminals</p> <p>screw-type terminals</p> |
| Type of connectable conductor cross-sections | |
| <ul style="list-style-type: none"> • for main contacts <ul style="list-style-type: none"> — solid — stranded — single or multi-stranded — finely stranded with core end processing — finely stranded without core end processing • at AWG conductors for main contacts | <p>2x (2.5 ... 16 mm²)</p> <p>2x (10 ... 50 mm²)</p> <p>2x (2,5 ... 16 mm²)</p> <p>2x (2.5 ... 35 mm²)</p> <p>2x (10 ... 35 mm²)</p> <p>2x (10 ... 1/0)</p> |
| Type of connectable conductor cross-sections | |
| <ul style="list-style-type: none"> • for auxiliary contacts <ul style="list-style-type: none"> — solid — finely stranded with core end processing • at AWG conductors for auxiliary contacts | <p>2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), max. 2x (0.75 ... 4 mm²)</p> <p>2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)</p> <p>2x (20 ... 16), 2x (18 ... 14), 1x 12</p> |

Certificates/approvals

| General Product Approval | | | | Declaration of Conformity | Test Certificates |
|--|--|---|---|---|---|
|  CCC |  CSA |  UL |  |  EG-Konf. | spezielle Prüfbescheinigungen |

| Shipping Approval | | | | | other |
|--|---|--|---|---|-------------------------------|
|  ABS |  GL |  LRS |  RINA |  RMRS | Bestätigungen |

| other |
|---|
| Umweltbestätigung sonstig |

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1046-1BB44>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1046-1BB44>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1046-1BB44>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1046-1BB44&lang=en



last modified:

09/20/2016