



Figure similar

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8138-1HF20-1BA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		P <sub>N</sub> [kW]	M <sub>N</sub> [Nm]	I <sub>N</sub> [A]	U <sub>N</sub> [V]	f <sub>N</sub> [Hz]	n <sub>N</sub> [rpm]	M <sub>max</sub> [Nm]	I <sub>max</sub> [A]	n <sub>max</sub> [rpm]	M <sub>0</sub> [Nm]	I <sub>0</sub> [A]	η	cos φ	I <sub>μ</sub> [A]
Y	ALM 400V	33.0	180.0	77.0	332	60.0	1,750	400	168.0	8,000	223.0	88	0.898	0.870	27.1
	BLM/SLM 400V	30.0	191.0	80.0	289	51.9	1,500	400	168.0	8,000	223.0	88	0.882	0.880	27.1
	ALM/BLM/SLM 480V	37.0	177.0	76.0	380	68.4	2,000	400	168.0	8,000	223.0	88	0.920	0.860	28.4

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Water cooling
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP65
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

### Cooling water specification

pH value	6 ... 9
Total hardness	1.7 mmol/l
Electrical conductivity	500 μS/cm
Chloride ions	40 mg/l
Sulfate ions	50 mg/l
Nitrate ions	50 mg/l
Dissolved substances	340 mg/l
Maximum particle size	100 μm
Antifreeze/corrosion protection	20 ... 30 %

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

### Physical constants

Thermal time constant	12 min
Moment of inertia	1,090 kgcm <sup>2</sup>
Weight (approx.)	157 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

### Cooling data and sound pressure level

Flow rate, min.	12 l/min
Sound pressure level L <sub>pA</sub> (1m) motor rated load, tolerance + 3dB	68 dB <sup>1)</sup>
Pressure drop	0.9 bar
NDE thread connection	0.375 Inches