

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV3083B

SIMOTICS GP - 80 M - IM B14 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_l/I_N	M_A/M_N T_l/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
DOL duty (S1) - 155(F) to 130(B)																	
220	Δ	60	0.86	-/-	3.60	1750	4.7	83.5	83.1	80.7	0.75	0.67	0.55	7.7	2.7	4.1	IE3
380	Y	60	0.86	-/-	2.10	1750	4.7	83.5	83.1	80.7	0.75	0.67	0.55	7.7	2.7	4.1	IE3
220	Δ	60	0.75	-/-	3.30	1760	4.0	83.5	82.6	79.7	0.71	0.63	0.50	8.3	3.1	4.7	IE3
380	Y	60	0.75	-/-	1.92	1760	4.0	83.5	82.6	79.7	0.71	0.63	0.50	8.3	3.1	4.7	IE3
IM B14 / IM 3601		FS 80 M		IP55		UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 19.8 s | 23.6 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	53 / 64 dB(A) ^{2) 3)}	53 / 64 dB(A) ^{2) 3)}	Vibration severity grade	A
Moment of inertia	0.0029 kg m ²		Thermal class	F
Bearing DE NDE	6004 2Z C3	6004 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} , $F_{Rad min}$ 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	14 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9 mm - 17 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	document type datasheet	document status released			document number
	title 1LE1003-0DB31-7KA4-Z D22	rev. 929	creation date 2022-10-18		
© Siemens AG 2022					

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS





Motor type : 1AV3083B

SIMOTICS GP - 80 M - IM B14 - 4p

Special design

D22 Motor without CE character for export outside the EEA (see EU regulation 2019/1781)

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents 
	document type datasheet		document status released		
	title 1LE1003-0DB31-7KA4-Z D22		document number		
© Siemens AG 2022		rev. 929	creation date 2022-10-18	language en	Page 2/2