

SECTION FUS-NH 3x 200 A SANS COMM

| Model | |
|--|-----------------------------------|
| product designation | switch disconnecter with fuses |
| design of the product | for NH 1 |
| fuse system | NH 1 |
| Supply voltage | |
| operating voltage at DC rated value | 220 V |
| Protection class | |
| protection class IP | IP00 |
| Main circuit | |
| operational current rated value | 200 A |
| suitability for use | Yes |
| • safety switch | |
| Connections | |
| type of electrical connection for main current circuit | BUSBAR CONNECTION |
| Mechanical Design | |
| height | 196 m |
| width | 235 m |
| depth | 113 m |
| fastening method | Surface mounting and installation |
| net weight | 5 kg |
| Environmental conditions | |
| ambient temperature during operation | |
| • minimum | -20 °C |
| • maximum | 45 °C |
| ambient temperature during storage minimum | -25 °C |
| General Product Approval | |
| | other |

[Confirmation](#)



[Environmental Con-
firmations](#)

[Miscellaneous](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KL7131-3AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KL7131-3AA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7131-3AA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



