

CONNECTING CABLE S7 GESCHIRMT 3.0M
 CONNECTING CABLE SHIELDED FOR SIMATIC S7-300/1500
 BETWEEN FRONT CONNECTOR MODULE A. TERMINAL BLOCK
 16 X 0.14MM2 WITH IDC CONNECTORS, LENGTH 3.0 M



Figure similar

Operating data

Operating voltage / at DC	
<ul style="list-style-type: none"> • Rated value • maximum 	<p>24 V</p> <p>60 V</p>
Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage 	<p>0 ... 60 °C</p> <p>-30 ... +70 °C</p>

General data

Suitability for interaction	
<ul style="list-style-type: none"> • Input card PLC • PLC output card 	<p>Yes</p> <p>Yes</p>
Suitability for use	
<ul style="list-style-type: none"> • digital signal transmission • analog signal transmission 	<p>Yes</p> <p>Yes</p>

Product properties, functions, components / general

Number of channels	8
--------------------	---

Wire length	3 m
Number of poles	16
Number of conductors / of connecting cable	16
Conductor cross section / Rated value	0.14 mm ²
Color / of cable sheath	Black
Outer diameter / of cable sheath	7 mm
Number of poles / at the 1st interface	16
Number of poles / at the 2nd interface	16
Certificate of suitability / cULus approval	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	0.25 kg

last modified: 10/20/2016