

Product type designation

C-PLUG 256

C-PLUG 256 (CP343-1 ADVANCED) REPLACEABLE MEDIUM FOR SIMPLE DEVICE EXCHANGE IN CASE OF FAILURE, FOR STORAGE OF CONFIGURATION OR USER DATA, 256MB, CAN BE USED IN CP343-1 ADVANCED



Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Width	24.3 mm
Height	17 mm
Depth	8.1 mm
Net weight	5 g
design of the removable storage	
• C-PLUG	Yes
• KEY-PLUG	No

Product properties, functions, components / general

Storage capacity	256 Mibyte
------------------	------------

Further Information / Internet Links

Internet-Link

- | | |
|---|---|
| • to website: TIA Selection Tool | http://www.siemens.com/tia-selection-tool |
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to the website: IWLAN | http://www.siemens.com/iwlan |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAx Download Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |

last modified:

10/19/2016