

S7-300 FRONT CON. W. SINGLE COR. 3.2 M  
 FRONT CONNECTOR FOR SIMATIC S7-300 40-POLE (6ES7392-1AM00-0AA0), WITH 40 SINGLE CORES 0.5 MM<sup>2</sup>, H05V-K SINGLE CORES, SCREW-TYPE VERSION, PACKING UNIT= 5 PCS., L = 3.2 M



Figure similar

Target system	SIMATIC S7-300
<b>Product properties, functions, components / general</b>	
Wire length	3.2 m
Color / of cable sheath	blue
Outer diameter / of cable sheath	2.2 mm
Conductor cross section / Rated value	0.5 mm <sup>2</sup>
Number of channels	40
Number of poles	40
<b>Operating data</b>	
Operating voltage / at DC	
• Rated value	24 V
• maximum	30 V
Continuous current / with simultaneous load on all cores / at DC / maximum permissible	1.5 A
Ambient temperature	
• during storage	-30 ... +70 °C
• during operation	0 ... 60 °C

## General data

Certificate of suitability / cULus approval	No
Suitability for interaction	
• Input card PLC	Yes
• PLC output card	Yes
Suitability for use	
• digital signal transmission	Yes
• analog signal transmission	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	6.5 kg