

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3317B

SIMOTICS SD - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Safe Area

-/-

Electrical data

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL	
								4/4	3/4	2/4	4/4	3/4	2/4					
DOL duty (S1) - 155(F) to 130(B)																		
400	Δ	50	315.00	-/-	570.00	1490	2000.0	96.0	96.0	95.6	0.83	0.80	0.70	8.5	3.2	3.5	IE3	
690	Y	50	315.00	-/-	330.00	1490	2000.0	96.0	96.0	95.6	0.83	0.80	0.70	8.5	3.2	3.5	IE3	
460	Δ	60	315.00	-/-	495.00	1792	1680.0	96.2	96.0	95.3	0.83	0.78	0.69	9.4	3.4	3.7	IE3	
460	Δ	60	360.00	-/-	560.00	1790	1920.0	96.2	96.1	95.6	0.84	0.80	0.72	8.3	3.0	3.2	IE3	
IM B3 / IM1001			FS 315 L			IP55		UKCA		IEC/EN 60034			IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1,000 m										Locked rotor time (hot / cold) : 20.7 s 41.4 s								

Mechanical data



Sound level (SPL / SWL) at 50Hz 60Hz	75 / 90 dB(A) ^{2) 3)}	81 / 95 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes	
Moment of inertia	5.3900 kg m ²		Vibration severity grade	Grade A	
Bearing DE NDE	6319 C4	6319 C4	Thermal class	F	
permissible lateral force on (N)	X_0 : 9300	$X_{0.5}$: 8650	X_{max} : 8000	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional	
L_{10mh} $F_{Rad, min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron	
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Net weight of the motor	1560 kg	
Lubricants	UNIREX N3		Coating (paint finish)	Standard paint finish C2	
Regreasing device	(Standard) Flat type lubricating nipple acc. DIN 3404		Color, paint shade	RAL7030	
Grease nipple	M10x1 DIN 3404 A		Motor protection	without (Standard)	
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled	
Condensate drainage holes	(Standard) Yes				

Terminal box

Terminal box position	box at the top, socket left	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	42 mm - 54 mm
Type of terminal box	TB3Q61	Cable entry	2xM63x1,5
Contact screw thread	6xM12	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L_{10mh} according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. IN LVM	technical reference	created by SPC	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents 
	document type datasheet	document status released			
	title 1LE5503-3AB73-4AA0	document number			
© INNOMOTICS 2023	rev. 951	creation date 2023-12-14	language en	Page 1/1	