

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8107-1HG03-1BC1



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

	$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$U_N$ [V]	$f_N$ [Hz]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]	$\eta$	$\cos \phi$	$I_{\mu}$ [A]	
Y	ALM 400V	12.0	50.0	26.0	406	78.6	2,300	120	60.0	9,000	63.0	29	0.909	0.780	13.0
	BLM/SLM 400V	10.5	50.0	26.0	355	68.6	2,000	120	60.0	9,000	63.0	29	0.897	0.780	12.9
	ALM 480V	13.7	47.0	24.0	480	95.1	2,800	120	60.0	9,000	63.0	29	0.920	0.770	12.8
	BLM/SLM 480V	13.0	47.0	24.0	460	90.0	2,650	120	60.0	9,000	63.0	29	0.932	0.770	12.8

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	100
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

### External fan

#### Max. power consumption

3 AC 400 V / 50 Hz ( $\pm 10\%$ )	0.10 A
3 AC 400 V / 60 Hz ( $\pm 10\%$ )	0.08 A
3 AC 480 V / 60 Hz ( $\pm 10\%$ )	0.11 A

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

### Physical constants

Thermal time constant	20 min
Moment of inertia	289 kgcm <sup>2</sup>
Weight (approx.)	73 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	NDE
Signal connection	left
Terminal box designation	gk813

### Cooling data and sound pressure level

Airflow, min.	0.04 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	110 Pa