

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8133-1FD03-OCA1



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

	$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$U_N$ [V]	$f_N$ [Hz]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]	$\eta$	$\cos \phi$	$I\mu$ [A]	
Y	ALM 400V	13.5	112.0	29.0	361	40.1	1,150	250	65.0	8,000	126.0	32	0.884	0.880	10.7
	BLM/SLM 400V	12.0	115.0	30.0	319	35.0	1,000	250	65.0	8,000	126.0	32	0.871	0.880	10.1
	ALM 480V	16.6	106.0	28.0	459	51.5	1,500	250	65.0	8,000	126.0	32	0.900	0.860	10.7
	BLM/SLM 480V	15.0	106.0	28.0	417	46.5	1,350	250	65.0	8,000	126.0	32	0.904	0.860	10.7

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Plain shaft
Encoder system	Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm

### External fan

#### Max. power consumption

3 AC 400 V / 50 Hz ( $\pm 10\%$ )	0.10 A
3 AC 400 V / 60 Hz ( $\pm 10\%$ )	0.12 A
3 AC 480 V / 60 Hz ( $\pm 10\%$ )	0.12 A

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

### Physical constants

Thermal time constant	30 min
Moment of inertia	760 kgcm <sup>2</sup>
Weight (approx.)	106 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

### Cooling data and sound pressure level

Airflow, min.	0.09 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	140 Pa