

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3317B

SIMOTICS SD - 315 L - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks **Safe Area**

Electrical data

-/-

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			cos φ ³⁾			I _A /I _N I _I /I _N	M _A /M _N T _I /T _N	M _K /M _N T _B /T _N	IE-CL	
								4/4	3/4	2/4	4/4	3/4	2/4					
DOL duty (S1) - 155(F) to 130(B)																		
400	Δ	50	315.00	-/-	570.00	1490	2000.0	96.0	96.0	95.6	0.83	0.80	0.70	8.5	3.2	3.5	IE3	
690	Y	50	315.00	-/-	330.00	1490	2000.0	96.0	96.0	95.6	0.83	0.80	0.70	8.5	3.2	3.5	IE3	
460	Δ	60	315.00	-/-	495.00	1792	1680.0	96.2	96.0	95.3	0.83	0.78	0.69	9.4	3.4	3.7	IE3	
460	Δ	60	360.00	-/-	560.00	1790	1920.0	96.2	96.1	95.6	0.84	0.80	0.72	8.3	3.0	3.2	IE3	
IM B3 / IM1001			FS 315 L			IP55		UKCA		IEC/EN 60034			IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1000 m										Locked rotor time (hot / cold) : 20.7 s 41.4 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	75 / 90 dB(A) ^{2) 3)}	81 / 95 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	5.3900 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6319 C4		Thermal class	F
permissible lateral force on (N) (N)	X ₀₂ : 9300	X ₀₅ : 8650	X _{max} : 8000	Duty type
bearing lifetime	L _{10mh} F _{Rad, min} for coupling operation 50 60Hz ¹⁾		Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	40 g 40 g 6000 h		Frame material	cast iron
Lubricants	UNIREX N3		Net weight of the motor	1560 kg
Regreasing device	Flat type lubricating nipple		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 3404 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Condensate drainage holes	(Standard) Yes		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	box at the top, socket right	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	42 mm - 54 mm
Type of terminal box	TB3Q61	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L_{10mh} according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	Document type Technical data sheet	Document status Released			
	Document title 1LE5603-3AB73-4AB1-Z	Document number TDS-240702-113201			
Restricted © Innomotics 2024	B12	Revision AA	Creation date 2024-07-02		

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3317B

SIMOTICS SD - 315 L - IM B3 - 4p

Special design

B12 Sea worthy packaging

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	Created by SPC	Approved by Created automatically	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>	Link documents
	Document type Technical data sheet	Document status Released			
	Document title 1LE5603-3AB73-4AB1-Z	Document number TDS-240702-113201			
Restricted © Innomotics 2024	B12	Revision AA	Creation date 2024-07-02		