

fixed-mounted molded case circuit breaker w. handle frame 1600; 4AUX and trip alarm switch S24; Icu "M" Icu=55kA @ 415V, 3-pole ETU660, LSIG, In=1600A display, meas., comm. function Ir=640...1600A I_{sd}=0.6...10xIn, I_i=1.5...15xIn N conductor protec. adjustable opt. w. ext. CT; up to 200% gr.-fault prot., can be sw. off I_g=0.1...1 x In, t_g=0.1 - 1.0s rear horizontal connection With optional communication connection including integrated breaker connect 24 V DC module, actuator COM ACT, COM RTC and COM PSS(as draw-out version) with Metering MF Basic for energy monitoring Voltage tap at the bottom Without additional alarm switch assembly With mechanical calling without 2nd auxiliary release without 1st auxiliary release F03= Communication module COM041 PROFINET Gateway T30= Door sealing frame IP30 for fixed-mounted circuit breaker

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2716-5CF02-0AA0-Z F03+T30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2716-5CF02-0AA0-Z F03+T30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2716-5CF02-0AA0-Z F03+T30

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

7/18/2024

