



Figure similar

## Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8228-1HF10-2EA1-Z**  
G14+L03

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		P <sub>N</sub> [kW]	M <sub>N</sub> [Nm]	I <sub>N</sub> [A]	U <sub>N</sub> [V]	f <sub>N</sub> [Hz]	n <sub>N</sub> [rpm]	M <sub>max</sub> [Nm]	I <sub>max</sub> [A]	n <sub>max</sub> [rpm]	M <sub>0</sub> [Nm]	I <sub>0</sub> [A]	η	cos φ	I <sub>μ</sub> [A]
Y	ALM 400V	179.0	977.0	330.0	395	58.7	1,750	2,450	750.0	4,500	977.0	330	0.961	0.820	170.0
	BLM/SLM 400V	160.0	1,019.0	340.0	340	50.4	1,500	2,450	750.0	4,500	1,019.0	340	0.959	0.830	170.0
	ALM/BLM/SLM 480V	196.0	936.0	325.0	450	67.1	2,000	2,450	750.0	4,500	36.0	325	0.962	0.810	169.0

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Increased cantilever forces
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

### Physical constants

Thermal time constant	55 min
Moment of inertia	23,300 kgcm <sup>2</sup>
Weight (approx.)	870 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7700-P02

### Cooling data and sound pressure level

Airflow, min.	0.31 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	650 Pa

### External fan

#### Max. power consumption

1 AC 200 ... 277 V (±10%) 50/60 Hz ±10%    2.0 ... 2.3 A

### Special design

G14 with air filter

L03 Version for increased vibration stress

<sup>1)</sup> at a rated frequency of 2 kHz and a speed range of up to 3500 rpm