



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8083-1DG02-0HE1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

	P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	$\cos \varphi$	I_{μ} [A]
Y	ALM 400V	4.1	17.0	11.3	332	80.0	45	24.0	10,000	21.0	12	0.852	0.780	5.7
	BLM/SLM 400V	3.7	17.7	11.6	293	70.2	45	24.0	10,000	21.0	12	0.832	0.790	5.7
	ALM 480V	4.8	16.4	11.3	400	96.4	45	24.0	10,000	21.0	12	0.868	0.760	5.7
	BLM/SLM 480V	4.6	16.6	11.2	376	91.6	45	24.0	10,000	21.0	12	0.862	0.780	5.7

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	80
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Plain shaft
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

External fan

Max. power consumption

1 AC 230 V / 50 Hz ($\pm 10\%$)	0.20 A
1 AC 230 V / 60 Hz ($\pm 10\%$)	0.16 A
1 AC 265 V / 60 Hz ($\pm 10\%$)	0.19 A

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Physical constants

Thermal time constant	10 min
Moment of inertia	64 kgcm ²
Weight (approx.)	32 kg

Connection

Type of electrical connection	Power connector
Position of the connection	Power connector, top
Power connection	right
Signal connection	DE

Cooling data and sound pressure level

Airflow, min.	0.02 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	95 Pa