



Circuit breaker 10kA, 2-pole, C, 6A according to UL 489-480Y/277V Multi-Unit Packaging (32 Stück)

Figure similar

Model	
product brand name	SENTRON
product designation	Miniature circuit breakers
design of the product	Miniature circuit-breaker 5SJ4
General technical data	
number of poles	2
design of pole	2P
tripping characteristic class	C
mechanical service life (operating cycles) typical	10 000
installation environment regarding EMC	Suitable for environment B (immunity to interference not applicable)
reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750	F
overvoltage category	3
degree of pollution	3
Voltage	
insulation voltage (U <sub>i</sub> ) at AC rated value	440 V
operational current	
• at 30 °C rated value	6 A
• at 40 °C rated value	6 A
• at 50 °C rated value	5.7 A
• at 55 °C rated value	5.6 A
• at 60 °C rated value	5.4 A
• at AC rated value	6 A
Supply voltage	
supply voltage	
• at AC	400 V
• at DC rated value	60 V
value range of the supply voltage frequency	50/60 Hz
operating voltage	
• at AC according to UL 489 and CSA C22.2 No. 5-02 maximum	277 V
• at DC rated value maximum	60 V
• at DC 1-channel according to UL 489 and CSA C22.2 No. 5-02 maximum	60 V
• at DC 2-channel according to UL 489 and CSA C22.2 No. 5-02 maximum	125 V
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20, with connected conductors, IP 40 in the handle range
Breaking Capacity	

switching capacity current		
<ul style="list-style-type: none"> <li>• according to EN 60898 rated value</li> <li>• according to IEC 60947-2 rated value</li> </ul>	 10 kA 15 kA	
<b>Dissipation</b>		
power loss [W] for rated value of the current at AC in hot operating state per pole	2.7 W	
<b>Main circuit</b>		
<b>type of voltage supply at AC according to UL 489 and CSA C22.2 No. 5-02</b>	480/277	
<b>suitability for operation</b>	Infrastructure / Industry	
<b>Product details</b>		
<b>product feature touch protection</b>	Yes	
product component		
<ul style="list-style-type: none"> <li>• tunnel terminals top</li> <li>• tunnel terminals bottom</li> <li>• combined terminal top</li> <li>• combined terminal bottom</li> <li>• neutral conductor switching</li> </ul>	 No No Yes Yes No	
<b>product feature</b>		
<ul style="list-style-type: none"> <li>• halogen-free</li> <li>• sealable</li> <li>• silicon-free</li> </ul>	 Yes Yes Yes	
product extension installable supplementary devices	Yes	
<b>Product function</b>		
<b>set values setting current (Ii) for I-tripping</b>	7,5	
<b>reference value setting current (Ii) for I-tripping</b>	x I <sub>n</sub>	
product function note	Terminal tightening torque for Cu, 60/75°C; 3.5Nm/31lb.in	
<b>Short circuit</b>		
short-circuit current breaking capacity (I <sub>cn</sub> ) at AC according to UL 1077 and CSA C22.2 No.235	10 kA	
<b>Connections</b>		
<b>connectable conductor cross-section finely stranded with core end processing</b>		
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	 0.8 mm <sup>2</sup> 25 mm <sup>2</sup>	
tightening torque with screw-type terminals maximum	3.5 N·m	
position of power supply cord	Any	
<b>Mechanical Design</b>		
<b>height</b>	121 mm	
<b>width</b>	36 mm	
<b>depth</b>	70 mm	
<b>installation depth</b>	70 mm	
<b>number of modular width units</b>	2	
<b>fastening method</b>	on standard mounting rail	
<b>mounting position</b>	any	
<b>net weight</b>	337 g	
<b>Environmental conditions</b>		
<b>standard</b>	IEC / EN 60947-2 / UL 489	
<b>vibration resistance</b>	50 m/s <sup>2</sup> at 25 to 150Hz and 60m/s <sup>2</sup> at 35Hz (4sec)	
vibration resistance according to IEC 60068-2-6	±1 mm at 5 to 25 Hz; 50 m/s <sup>2</sup> at 25 to 150 Hz	
<b>ambient temperature during operation</b>		
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	 -25 °C 55 °C	
<b>ambient temperature during operation</b>	max. 95% humidity	
<b>ambient temperature during storage</b>		
<ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>	 -40 °C 75 °C	
<b>Approvals Certificates</b>		
<b>General Product Approval</b>	<b>Test Certificates</b>	<b>other</b>



Environment

[Environmental Confirmations](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SJ4206-7HG42-Z W12>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SJ4206-7HG42-Z W12>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SJ4206-7HG42-Z W12](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SJ4206-7HG42-Z W12)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

8/22/2024

