



Power semiconductor module 600 V, for 3RW52/50, 315 A

product designation	Power semiconductor module
design of the product	600 V, 315 A
manufacturer's article number of soft starter	
•	3RW5073 (2x), 3RW5074 (2x)
•	3RW5144 (3x), 3RW5145 (3x)
•	3RW5244 (3x), 3RW5245 (3x)

General technical data

Substance Prohibitation (Date)	02/15/2018
Weight	120 g

Ambient conditions

ambient temperature during storage	-40 ... +80 °C
------------------------------------	----------------

Approvals Certificates

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



[Confirmation](#)



EG-Konf.



[KC](#)

[Miscellaneous](#)

Test Certificates	Marine / Shipping	other
-------------------	-------------------	-------

[Type Test Certificates/Test Report](#)



ABS



DNV



LRS



PRS

[Confirmation](#)

Environment

[Environmental Confirmations](#)

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5924-0SQ05>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5924-0SQ05>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5924-0SQ05>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5924-0SQ05&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5924-0SQ05/char>

Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5924-0SQ05&objecttype=14&gridview=view1>

Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

1/18/2021 

