



Figure similar

MLFB-Ordering data

6SL3210-5DE22-0UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data

Input

Number of phases	3 AC
Line voltage	380 ... 480 V -15 % +10 %
Line frequency	45 ... 66 Hz

Output

Rated power	7.50 kW
Rated current (IN)	19.60 A
Max. output current	39.20 A

Electronic power supply

Power supply	24 V ±10 %
--------------	------------

Connections

Motor end

Conductor cross-section	4.0 mm ²
-------------------------	---------------------

Mechanical data

Degree of protection	IP20 / UL open type
Frame size	FSC
Net weight	5.05 kg (11.13 lb)
Width	140.0 mm (5.51 in)
Height	260.0 mm (10.24 in)
Depth	240.0 mm (9.45 in)

Ambient conditions

Cooling	Forced-air cooling via fan
Installation altitude	1000 m
Cooling air requirement	0.005 m ³ /s (0.177 ft ³ /s)

Ambient temperature

Operation	0 ... 45 °C (32 ... 113 °F)
Storage	-40 ... 70 °C (-40 ... 158 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)

Relative humidity

Max. operation	90 %
----------------	------

Standards

Compliance with standards	CE
---------------------------	----