

touch pen caps V2A, replacement caps for touch pen system for capacitive and resistive touch screens, scope of supply: 5 touch pen caps



Figure similar

| General information | |
|---|---|
| Product type designation | Touch pen caps |
| Control elements | |
| Frame size/design | |
| <ul style="list-style-type: none"> Standard | Yes; threaded special cap for universal touch system |
| Installation type/mounting | |
| Wall mounting/direct mounting | Yes; can be used for touch pen system ELO and V2A |
| Standards, approvals, certificates | |
| CE mark | No; No CE marking obligation |
| RoHS conformity | Yes; FDA§177.2600 compliant |
| FDA-compliant | Yes; FDA§177.2600 compliant |
| Ambient conditions | |
| Suited for indoor use | Yes |
| Suited for outdoor use | Yes; only suitable under certain conditions due to different environmental conditions; replacement cycle can be increased |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> min. | -40 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended |
| <ul style="list-style-type: none"> max. | 80 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> min. | -40 °C |
| <ul style="list-style-type: none"> max. | 80 °C |
| Relative humidity | |
| <ul style="list-style-type: none"> Operation, max. | 95 % |
| Accessories | |
| belongs to product | can be used for touch pen system ELO and V2A |
| Mechanics/material | |
| Material | |
| <ul style="list-style-type: none"> Plastic | Yes; special cap only for resistive and capacitive touch systems |
| <ul style="list-style-type: none"> Stainless steel | Yes; food safe, suitable for F&B |
| Color | stainless steel, polished |
| Torques/forces | |
| <ul style="list-style-type: none"> Tightening torque, max. | Hand-tight |
| Dimensions | |
| Height | 8 mm |
| Diameter | 8 mm |
| Weights | |
| Weight (without packaging) | 0.8 g |
| Weight (with packaging) | 1.7 g |

| Scope of supply | |
|-----------------------------|---|
| Delivery quantity in pieces | 5; Caps for touch pen |
| Other | |
| Merchandise | Yes; touch replacement cap V2A |
| Manufacturer name | QUERUM products UG |
| Manufacturer's address | Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany |
| contacting the manufacturer | email: querumproducts@web.de |
| Target devices | For common capacitive and resistive touch systems |
| Note: | food safe, suitable for F&B |

| Classifications | | | |
|-----------------|--------|---------|----------------|
| | | Version | Classification |
| | eClass | 14 | 27-33-02-92 |
| | eClass | 12 | 27-33-02-92 |
| | eClass | 9.1 | 27-33-02-92 |
| | eClass | 9 | 27-33-02-92 |
| | eClass | 8 | 27-24-92-03 |
| | eClass | 7.1 | 27-24-92-03 |
| | eClass | 6 | 27-24-92-03 |
| | ETIM | 9 | EC002584 |
| | ETIM | 8 | EC002584 |
| | ETIM | 7 | EC002584 |
| | IDEA | 4 | 3552 |
| | UNSPSC | 15 | 32-15-17-03 |

Further information
 Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415
<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified: 5/22/2024 