



## P2RF-08-S

Socket, DIN rail/surface mounting, 8-pin, screwless terminals

# Specifications

Applicable product family	G2R-2-S
Mounting method	DIN rail/screw
Product Depth (unpacked)	32.6 mm
Product Height (unpacked)	92 mm
Product Width (unpacked)	18 mm
Terminal type	Screwless clamp
Color	Beige
Hold down clip included	✓
Release Lever included	✓
Applicable ferrules	Forked terminals, Round terminals

## Fits to



**G2R-2-S 110VAC (S)**  
Relay, plug-in, DPDT, 5 A,  
mechanical indicator, 110  
VAC



**G2R-2-S 12VDC (S)**  
Relay, plug-in, 8-pin, DPDT,  
10 A, mech indicator, label  
facility, 12 VDC



**G2R-2-S 220VAC (S)**  
Relay, plug-in, 5 A,  
mechanical indicator, 220  
VAC



**G2R-2-S 230VAC (S)**  
Relay, plug-in, DPST, 10 A,  
mechanical indicator, 230  
VAC

**G2R-2-S 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 240 VAC

**G2R-2-S 24VAC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 24 VAC

**G2R-2-S 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, label facility, 24 VDC

**G2R-2-SD 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech indicators, coil suppressor, label facility

**G2R-2-SN 110VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 110 VAC

**G2R-2-SN 110VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 110 VDC

**G2R-2-SN 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 120 VAC

**G2R-2-SN 12VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 12 VAC

**G2R-2-SN 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 12 VDC

**G2R-2-SN 230VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 230 VAC

**G2R-2-SN 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 240 VAC

**G2R-2-SN 24VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 24 VAC

**G2R-2-SN 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 24 VDC

**G2R-2-SN 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 48 VDC

**G2R-2-SN-AP3 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, LED indicator

**G2R-2-SND 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility, 12 VDC



**G2R-2-SND 24VDC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility



**G2R-2-SND 48VDC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility, 48 VDC



**G2R-2-SND-AP3 24VDC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, mech & LED indicators, coil suppressor, label facility



**G2R-2-SNDI 12VDC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility, 12 VDC.



**G2R-2-SNDI 24VDC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility



**G2R-2-SNDI 48VDC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility




**G2R-2-SNDI-AP3 24VDC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label test button, Au-plating



**G2R-2-SNI 110VAC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



**G2R-2-SNI 120VAC (S)**  
Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 120 VAC



**G2R-2-SNI 12VAC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



**G2R-2-SNI 12VDC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility, 12 VDC



**G2R-2-SNI 230VAC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



**G2R-2-SNI 240VAC (S)**  
Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 240 VAC



**G2R-2-SNI 24VAC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



**G2R-2-SNI 24VDC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



**G2R-2-SNI 48VAC (S)**  
Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



### **G2R-2-SNI 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility



### **G2R-2-SNI-AP3 230VAC (S)**

Relay, plug-in, DPDT (gold plated), 5 A, mech. & LED indicator, test button, 230 VAC

## Accessories



**P2CM-S**

Clip for use with P2RF-S



**P2RM-SB**

Socket bridge (for use with P2RF\_S), one pack including 50 bridges

**PFP-S**

Spacer



**XW5Z-EP12**

Separator Plate for terminal blocks, 12 mm width

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### G2R-\_-S (S) General- purpose Relay Datasheet

EN PDF 3.33 MB



### G3R-I/O Solid State Relays Datasheet

EN PDF 2.96 MB



### H3RN Solid-state Timer Datasheet

EN PDF 2.13 MB



### H3RN-\_-B Solid-state timer Datasheet

EN PDF 1.59 MB



### K7L-AT50(D) Liquid Leakage Sensor Amplifiers Datasheet

EN PDF 640 KB



### K7L-series Liquid Leakage Sensor Amplifiers Datasheet

EN PDF 7.08 MB



### P2RF-05-ESS Relay Sockets Datasheet

EN PDF 496 KB



### P2RF-08-ESS Relay Sockets Datasheet

EN PDF 480 KB



### PYC-TR Relay Sockets Datasheet

EN PDF 198 KB



### PYF-\_-PU/PTF-\_- PU/P2RF-\_-PU Sockets with Push-In Plus technology Datasheet

EN PDF 2.59 MB