



NX-PF0730

NX I/O power feed unit, 5-24 V DC input, 8 terminals, 10 A, screwless push-in connector, 12 mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Power feed
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Number of IOV (V+) terminals	4
Number of IOG (V-) terminals	4
Number of FG terminals	0
Degree of protection (IP)	IP20
Product Height (unpacked)	104.5 mm
Product Width (unpacked)	12 mm
Product Depth (unpacked)	80.1 mm
Product Weight (unpacked)	65 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)



NX-TBA082

Replacement screwless push-in connector with 8 wiring terminals (marked A+B)

Downloads

CAD Library



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**IO-Link Series
Brochure**

EN PDF 7.5 MB



**Machine Safety Solution
Brochure**

EN PDF 2.86 MB



**NX-ECT 101
Users Manual**

EN PDF 7.35 MB



**NX-HAD
Brochure**

EN PDF 1.22 MB



**NX-HTC/NX-TC/EJ1/E5DC-B
Temperature control
units**

Flyer

EN PDF 3.28 MB



**NX-series I/O system
Brochure**

EN PDF 8.37 MB



**NX-series System Unit -
NX-PD/PF/PC/TBX**

Datasheet

EN PDF 3.25 MB



**Omron GX-JC0x-x
EtherCAT Junction Box**

EtherCAT ESI file

EN ZIP 3.36 KB



**Omron NX-ECC20x
EtherCAT ESI file**

EN ZIP 1.51 MB



**PLC I/O Interface Wiring
System Selection**

System Manual

EN PDF 1.56 MB



**Sysmac
Catalogue**

EN PDF 43.5 MB



**Sysmac: A Fully
Integrated Platform**

Brochure

EN PDF 19.1 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 1 July, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU