



P2RFZ-05-E

Socket, DIN rail/surface mounting, 5-pin, screw terminals

Specifications

Applicable product family	G2R-1-S
Mounting method	DIN rail/screw
Product Depth (unpacked)	61.0 mm
Product Height (unpacked)	79 mm
Product Width (unpacked)	15.5 mm
Terminal type	Screw
Color	Black
Hold down clip included	✓
Release Lever included	✓
Applicable ferrules	Forked terminals, Round terminals

Fits to



G2R-1-S 120VAC (S)
Relay, plug-in, SPDT, 10 A,
mechanical indicator, 120
VAC



G2R-1-S 12VDC (S)
Relay, plug-in, SPDT, 10 A,
mechanical indicator, 12
VDC



G2R-1-S 230VAC (S)
Relay, plug-in, 5-pin, SPDT,
10 A, mech indicator, label
facility, 230 VAC



G2R-1-S 24VAC (S)
Relay, plug-in, 5-pin, SPDT,
10 A, mech indicator, label
facility, 24 VAC



G2R-1-SD 24VDC (S)

Relay, plug-in, SPDT, 10 A, mech. indicator, diode, 24 VDC



G2R-1-SN 120VAC (S)

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, 120 VAC




G2R-1-SN-AP3 230VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating



G2R-1-SN-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, gold-plated contacts, LED indicator



G2R-1-SND 48VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility



G2R-1-SND-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating



G2R-1-SNDI 12VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, lockable test button, label facility, 12 VDC



G2R-1-SNDI-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A gold plate contacts, mech & LED indicators, coil suppressor, lockable test button, label facility



G2R-1-SNI 110VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility, 110 AC



G2R-1-SNI 120VAC (S)

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, test button, 120 VAC



G2R-1-SNI 230VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility



G2R-1-SNI 48VAC (S)

Relay, plug-in, SPDT, 10 A, mechanical & LED indicator, lockable testbutton, 48 VAC

Accessories



P2DN-CP100

Box of 100 caps for P2DN short bar: insulation cap for the short bar cut, blue color



PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

PFP-100N2

DIN-rail mounting track, 35x16mm, 1m length



PFP-50N

Din rail track, 500 mm



PFP-M

End plate

PFP-S

Spacer



XW5Z-EP12

Separator Plate for terminal blocks, 12 mm width



XW5Z-EP6

End bracket for terminal blocks, 6 mm width

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



G2R_-S (S) General- purpose Relay Datasheet

EN PDF 3.33 MB