



130B1296 [↗](#)

VLT® Modbus TCP MCA 122, coated

This product is not available in this store. Please contact your local [Customer Service Center](#).

**Customer Service Center** [↗](#)

The first industrial Ethernet-based protocol for automation. Connects to Modbus-TCP-based networks. Able to handle connection interval down to 5 ms in both directions, positioning it among the fastest performing Modbus TCP devices in the market. For master redundancy it features hot swapping between two masters.

PRODUCT DETAILS

Gross weight		0.63 Kilogram
Net weight		0.556 Kilogram
Volume		3.549 Cubic decimeter
EAN		5710107611065
DrivePro category	RECOMMENDED	Recommended spare part
	SELF SERVICE	Self-service spare part
	SPAREPART	Spare Part
Options	ACIBO	Interface board options

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit [store.danfoss.com](#).

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.