




 PRODUCT-DETAILS

DDA204 AC S-63/0.3

Residual Current Device Block - 4P - Type AC - 300 mA - 63 A



General Information

Extended Product Type	DDA204 AC S-63/0.3
Product ID	2CSB204901R3630
EAN	8012542810407
Catalog Description	Residual Current Device Block - 4P - Type AC - 300 mA - 63 A
Long Description	The RCD block DDA200 series is suitable for assembly with MCBs S200 series and S300P. It assures protection against the effects of sinusoidal alternating earth fault currents, protection, against indirects contacts and additional protection against direct contacts. Applications: residential, commercial, industrial.

ABB EcoSolutions

ABB EcoSolutions	Yes
EcoSolutions Profile	9AKK108471A0995
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 69.47 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill UL 2799 Zero Waste To Landfill Validation available
Sustainable Material Content in Packaging	Recycled Cardboard - 85.84 % Recycled Paper - 0 %

(wt. %)	Recycled Paper - 0 %
Extended Product Lifetime	Product Durability
End Of Life Disassembling Instructions	9AKK108469A7485
Environmental Product Declaration - EPD	9AKK108469A8934

Technical

Type of Residual Current	Type AC
Number of Poles	4P
Number of Modular Spacings per DIN Rail	8
Operating Characteristic	Selective

Electrical

Rated Operational Voltage	230/400 V
Rated Current (I_n)	63 A
Rated Residual Current	300 mA
Rated Frequency (f)	50 ... 60 Hz
Power Loss	7.6 W

Design

Number of Modules	8
-------------------	---

Material Compliance

RoHS Information	9AKK106713A5614
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20070731
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Environmental

Resistance to Vibrations	20 Cycles with Load 0.8 In: 1g or 1mm 50 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g / 2 shocks / 13 ms
Environmental Information	document not needed

Dimensions

Product Net Width	140 mm
Product Net Height	93 mm
Product Net Depth / Length	76 mm
Product Net Weight	0.290 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.394 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5614
--------------------------------	-----------------

Installation

Instructions and Manuals	9AKK106930A4375
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

External Classifications and Standards

ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 10	EC002297 - Residual current circuit breaker (RCCB) module
eClass	V11.0 : 27142210
Object Classification Code	F
Standards	EN 61009 Ann. G

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCD Blocks

