

## Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7132-5SC71-1CB0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed	2,000 rpm
Number of poles	8
Rated torque (100 K)	126.0 Nm
Rated current	55.00 A
Static torque (60 K)	120.0 Nm
Static torque (100 K)	140.0 Nm
Stall current (60 K)	50.00 A
Stall current (100 K)	60.00 A
Rotor moment of inertia	512.00 kgcm <sup>2</sup>
Efficiency	95.0 %

### Physical constants

Torque constant	2.42 Nm/A
Voltage constant at 20° C	165.0 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.09 Ω
Rotary field inductance	2.4 mH
Electrical time constant	28.00 ms
Mechanical time constant	2.00 ms
Thermal time constant	20 min
Shaft torsional stiffness	231,000 Nm/rad
Net weight of the motor	93.0 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	132
Cooling	Forced ventilation
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.125 mm
Axial runout tolerance	0.125 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Fitted key and keyway
Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Electrical connection	Transverse facing to right site
Connector size	3

### Optimum operating point

Optimum speed	2,000 rpm
Optimum power	26.5 kW

### Limiting data

Max. permissible speed (mech.)	3,600 rpm
Max. permissible speed (inverter)	3,500 rpm
Maximum torque	305.0 Nm
Maximum current	147.00 A

### Recommended Motor Module

Rated inverter current	60.00 A
Maximum inverter current	113.00 A
Maximum torque	245.0 Nm

### Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	140.0 Nm
Braking torque	60.0 Nm
Power supply voltage	DC 24 V
Coil current	1.80 A
Permissible brake work	9,800 J
Opening time	350 ms
Closing time	70 ms