

PT 2X2-24DC-ST - Surge protection plug



2838228

<https://www.phoenixcontact.com/gb/products/2838228>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PT protective connector with protective circuit for two 2-wire floating signal circuits. 24 V DC nominal voltage. HART-compatible.

Your advantages

- Easy testing and documentation with CHECKMASTER 2 with pluggable protective modules
- Maximum ease of maintenance, thanks to the 2-piece design
- Easy selection for all possible demands in MCR applications with a complete product portfolio
- The signal is not influenced during maintenance work, thanks to the impedance-neutral insertion and removal of protective plugs

Commercial data

Item number	2838228
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	CL2111
Product key	CL2111
GTIN	4017918182649
Weight per piece (including packing)	25.54 g
Weight per piece (excluding packing)	21.29 g
Customs tariff number	85363010
Country of origin	DE

PT 2X2-24DC-ST - Surge protection plug



2838228

<https://www.phoenixcontact.com/gb/products/2838228>

Technical data

Notes

General

Note	Technical data is valid in association with the following specified base elements:
	PT 2X2+F-BE 2839224
	PT 2X2-BE 2839208

Product properties

Product type	Surge protection for MCR technology
Product family	PLUGTRAB PT
IEC test classification	C1
	C2
	C3
	D1
Type	Male
Surge protection fault message	none
Arrester can be tested with CHECKMASTER from software version:	From SW rev. 1.00
Wire pairs per module	2

Insulation characteristics

Overvoltage category	III
Pollution degree	2


Electrical properties

Nominal voltage U_N	24 V DC
-----------------------	---------

Connection data

Connection method	Screw connection (in connection with the base element)
Screw thread	M3
Tightening torque	0.5 Nm
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 12

Dimensions

Dimensional drawing	
Width	17.5 mm

PT 2X2-24DC-ST - Surge protection plug



2838228

<https://www.phoenixcontact.com/gb/products/2838228>

Height	44.8 mm
Depth	51.7 mm
Horizontal pitch	1 Div.
Complete module width	17.7 mm
Complete module height	90 mm
Complete module depth	65.5 mm

Material specifications

Color	black (RAL 9005) copper color
Flammability rating according to UL 94	V-0
Housing material	PA 6.6

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Protective circuit

Direction of action	Line-Line & Line-Signal Ground/Shield & optional Signal Ground/Shield-Earth Ground
Maximum continuous operating voltage U_C	28 V DC 20 V AC
Rated current	450 mA (45 °C)
Operating effective current I_C at U_C	$\leq 5 \mu A$
Protective conductor current I_{PE}	$\leq 1 \mu A$ (with PT 2X2+F-BE) $\leq 4 \mu A$ (with PT 2X2-BE)
Nominal discharge current I_n (8/20) μs (line-line)	10 kA
Nominal discharge current I_n (8/20) μs (line-ground)	10 kA
Pulse discharge current I_{imp} (10/350) μs	2.5 kA
Total discharge current I_{Total} (8/20) μs	20 kA
Max. discharge current I_{max} (8/20) μs maximum (line-line)	10 kA
Max. discharge current I_{max} (8/20) μs maximum (line-earth)	10 kA
Nominal pulse current I_{an} (10/1000) μs (line-line)	25 A
Output voltage limitation at 1 kV/ μs (line-line) spike	$\leq 45 V$
Output voltage limitation at 1 kV/ μs (line-earth) spike	$\leq 450 V$ (with PT 2X2-BE) $\leq 1 kV$ (with PT 2X2+F-BE)
Output voltage limitation at 1 kV/ μs (line-line) static	$\leq 40 V$
Output voltage limitation at 1 kV/ μs (line-earth) static	$\leq 25 V$ (with PT 2X2-BE) $\leq 50 V$ (with PT 2X2+F-BE)
Residual voltage at I_n (conductor-conductor)	$\leq 40 V$
Residual voltage at I_n (line-signal ground)	$\leq 450 V$
Residual voltage with I_{an} (10/1000) μs (line-line)	$\leq 50 V$
Voltage protection level U_p (line-line)	$\leq 70 V$ (C1 - 1 kV / 500 A) $\leq 60 V$ (C2 - 6 kV / 3 kA)

PT 2X2-24DC-ST - Surge protection plug



2838228

<https://www.phoenixcontact.com/gb/products/2838228>

	≤ 70 V (C2 - 10 kV / 5 kA)
	≤ 50 V (C3 - 25 A)
Voltage protection level U_p (line-earth)	≤ 450 V (C1 - 1 kV / 500 A with PT 2X2-BE)
	≤ 500 V (C2 - 6 kV / 3 kA with PT 2X2-BE)
	≤ 550 V (C2 - 10 kV / 5 kA with PT 2X2-BE)
	≤ 1000 V (C2 - 10 kV / 5 kA with PT 2X2+F-BE)
Voltage protection level U_p static (line-line)	≤ 40 V (C2 - 10 kV / 5 kA)
Voltage protection level U_p static (line-earth)	≤ 50 V (C2 - 10 kV / 5 kA with PT 2X2-BE)
	≤ 100 V (C2 - 10 kV / 5 kA with PT 2X2+F-BE)
Response time t_A (line-line)	≤ 1 ns
Response time t_A (line-earth)	≤ 100 ns
Input attenuation aE, sym.	typ. 0.5 dB (≤ 1 MHz / 50 Ω)
	typ. 0.3 dB (≤ 400 kHz / 150 Ω)
	typ. 0.1 dB (≤ 70 kHz/600 Ω)
Cut-off frequency f_g (3 dB), sym. in 50 Ω system	typ. 4.5 MHz
Cut-off frequency f_g (3 dB), sym. in 150 Ω system	typ. 1.5 MHz
Cut-off frequency f_g (3 dB), sym. in 600 Ω system	typ. 600 kHz
Capacity (Core-Core)	typ. 1.4 nF
Capacity (Core-Earth)	typ. 8 pF (with PT 2X2-BE)
	typ. 2 pF (with PT 2X2+F-BE)
Resistance per path	2.2 Ω ±10 %
Surge protection fault message	none
Max. required back-up fuse	500 mA (T)
Impulse durability (line-line)	C1 - 1 kV / 500 A
	C2 - 6 kV / 3 kA
	C2 - 10 kV / 5 kA
	C3 - 25 A
Impulse durability (line-earth)	C1 - 1 kV / 500 A
	C2 - 6 kV / 3 kA
	C2 - 10 kV / 5 kA
	D1 - 2.5 kA

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	≤ 2000 m (amsl)

Standards and regulations

Standards/specifications	IEC 61643-21
Note	2000 + corrigendum 2001 + A1:2008, modified + A2:2012
Standards/specifications	EN 61643-21
Note	2001 + A1:2009 + A2:2013

PT 2X2-24DC-ST - Surge protection plug



2838228

<https://www.phoenixcontact.com/gb/products/2838228>

Mounting

Mounting type	on base element
---------------	-----------------


PT 2X2-24DC-ST - Surge protection plug

2838228

<https://www.phoenixcontact.com/gb/products/2838228>


Drawings

Dimensional drawing



The figure shows the complete module consisting of a base element and connector

Diagram




PT 2X2-24DC-ST - Surge protection plug

2838228

<https://www.phoenixcontact.com/gb/products/2838228>



Circuit diagram



PT 2X2-24DC-ST - Surge protection plug



2838228

<https://www.phoenixcontact.com/gb/products/2838228>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/2838228>



DNV GL

Approval ID: TAE00001N6



UL Listed

Approval ID: FILE E 138168

Nominal voltage U_N

Nominal current I_N

Cross section AWG

Cross section mm^2

24 V

0.45 A

-

-



cUL Listed

Approval ID: FILE E 333250



UL Listed

Approval ID: FILE E 333250

PT 2X2-24DC-ST - Surge protection plug



2838228

<https://www.phoenixcontact.com/gb/products/2838228>

Classifications

ECLASS

ECLASS-13.0	27171501
ECLASS-15.0	27171501

ETIM

ETIM 9.0	EC000943
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

PT 2X2-24DC-ST - Surge protection plug



2838228

<https://www.phoenixcontact.com/gb/products/2838228>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	419f8b28-e02f-4d7d-bb18-ed5b30ddfb60

EF3.0 Climate Change

CO2e kg	0.674 kg CO2e
---------	---------------

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk