


# UTTB 4 - Double-level terminal block



3044814

<https://www.phoenixcontact.com/gb/products/3044814>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Double-level terminal block, nom. voltage: 800 V, nominal current: 30 A, connection method: Screw connection, 1st and 2nd level, Rated cross section: 4 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: gray

## Your advantages

- Since there are two function shafts per level, all potential distribution tasks can be implemented quickly
- For a clear overview, each terminal point supports large-surface labeling
- As an option, the levels can be connected using the FBS-PV UT vertical bridge
- For example, two separate potentials can be routed side by side with the help of bridging between non-adjacent terminal blocks
- Tested for railway applications

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3044814       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | BE1114        |
| Product key                          | BE1114        |
| GTIN                                 | 4046356055512 |
| Weight per piece (including packing) | 19.366 g      |
| Weight per piece (excluding packing) | 18.434 g      |
| Customs tariff number                | 85369010      |
| Country of origin                    | DE            |

# UTTB 4 - Double-level terminal block



3044814

<https://www.phoenixcontact.com/gb/products/3044814>

## Technical data

### Product properties

|                       |                            |
|-----------------------|----------------------------|
| Product type          | Multi-level terminal block |
| Product family        | UT                         |
| Area of application   | Railway industry           |
|                       | Machine building           |
|                       | Plant engineering          |
|                       | Process industry           |
| Number of connections | 4                          |
| Number of rows        | 2                          |
| Potentials            | 2                          |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 1.02 W |

### Connection data

|                                 |                   |
|---------------------------------|-------------------|
| Number of connections per level | 2                 |
| Nominal cross section           | 4 mm <sup>2</sup> |

### 1st and 2nd level

|                                                                                           |                                                       |
|-------------------------------------------------------------------------------------------|-------------------------------------------------------|
| Screw thread                                                                              | M3                                                    |
| Tightening torque                                                                         | 0.6 ... 0.8 Nm                                        |
| Stripping length                                                                          | 9 mm                                                  |
| Internal cylindrical gage                                                                 | A4                                                    |
| Connection in acc. with standard                                                          | IEC 60947-7-1                                         |
| Conductor cross section rigid                                                             | 0.14 mm <sup>2</sup> ... 6 mm <sup>2</sup>            |
| Cross section AWG                                                                         | 26 ... 10 (converted acc. to IEC)                     |
| Conductor cross section flexible                                                          | 0.14 mm <sup>2</sup> ... 6 mm <sup>2</sup>            |
| Conductor cross section, flexible [AWG]                                                   | 26 ... 10 (converted acc. to IEC)                     |
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup>            |
| Flexible conductor cross section (ferrule with plastic sleeve)                            | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup>            |
| 2 conductors with same cross section, solid                                               | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>          |
| 2 conductors with same cross section, flexible                                            | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>          |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>          |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>           |
| Nominal current                                                                           | 30 A                                                  |
| Maximum load current                                                                      | 36 A (with 6 mm <sup>2</sup> conductor cross section) |

# UTTB 4 - Double-level terminal block



3044814

<https://www.phoenixcontact.com/gb/products/3044814>

|                       |                   |
|-----------------------|-------------------|
| Nominal voltage       | 800 V             |
| Nominal cross section | 4 mm <sup>2</sup> |

## Ex data

### Rated data (ATEX/IECEx)

|                                                                          |                                     |
|--------------------------------------------------------------------------|-------------------------------------|
| Identification                                                           | Ex II 2 GD Ex eb IIC Gb             |
| Operating temperature range                                              | -60 °C ... 110 °C                   |
| Ex-certified accessories                                                 | 3047293 D-UTTB 2,5/4                |
|                                                                          | 3047303 DP-UTTB 2,5/4               |
|                                                                          | 3047316 ATP-UTTB 2,5/4              |
|                                                                          | 1212587 SF-SL 0,6X3,5-100 S-VDE     |
|                                                                          | 3022276 CLIPFIX 35-5                |
|                                                                          | 3022218 CLIPFIX 35                  |
| List of bridges                                                          | Plug-in bridge / FBS 2-6 / 3030336  |
|                                                                          | Plug-in bridge / FBS 3-6 / 3030242  |
|                                                                          | Plug-in bridge / FBS 4-6 / 3030255  |
|                                                                          | Plug-in bridge / FBS 5-6 / 3030349  |
|                                                                          | Plug-in bridge / FBS 10-6 / 3030271 |
|                                                                          | Plug-in bridge / FBS 20-6 / 3030365 |
| Bridge data                                                              | 25.5 A / 4 mm <sup>2</sup>          |
| Ex temperature increase                                                  | 40 K (28.5 A / 4 mm <sup>2</sup> )  |
| for bridging with bridge                                                 | 440 V                               |
| - At bridging between non-adjacent terminal blocks                       | 275 V                               |
| - At bridging between non-adjacent terminal blocks via PE terminal block | 275 V                               |
| - At cut-to-length bridging with cover                                   | 220 V                               |
| - At cut-to-length bridging with partition plate                         | 176 V                               |
| Rated insulation voltage                                                 | 400 V                               |
| output                                                                   | (Permanent)                         |

### Ex level General

|                      |        |
|----------------------|--------|
| Rated voltage        | 440 V  |
| Rated current        | 25.5 A |
| Maximum load current | 31.5 A |

### Ex connection data General

|                                                    |                                              |
|----------------------------------------------------|----------------------------------------------|
| Torque range                                       | 0.6 Nm ... 0.8 Nm                            |
| Nominal cross section                              | 4 mm <sup>2</sup>                            |
| Rated cross section AWG                            | 12                                           |
| Connection capacity rigid                          | 0.14 mm <sup>2</sup> ... 6 mm <sup>2</sup>   |
| Connection capacity AWG                            | 26 ... 10                                    |
| Connection capacity flexible                       | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup>   |
| Connection capacity AWG                            | 26 ... 12                                    |
| 2 conductors with same cross section, solid        | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| 2 conductors with the same cross-section AWG rigid | 26 ... 16                                    |

# UTTB 4 - Double-level terminal block



3044814

<https://www.phoenixcontact.com/gb/products/3044814>

|                                                       |                                              |
|-------------------------------------------------------|----------------------------------------------|
| 2 conductors with same cross section, stranded        | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| 2 conductors with the same cross-section AWG flexible | 26 ... 16                                    |
| output                                                | (Permanent)                                  |

## Ex level Level 1

|                    |             |
|--------------------|-------------|
| Contact resistance | 0.35 mΩ     |
| output             | (Permanent) |

## Ex level Level 2

|                    |        |
|--------------------|--------|
| Contact resistance | 0.2 mΩ |
|--------------------|--------|

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 6.2 mm  |
| End cover width    | 2.2 mm  |
| Height             | 69.9 mm |
| Depth on NS 35/7,5 | 65 mm   |
| Depth on NS 35/15  | 72.5 mm |

## Material specifications

|                                                                  |                 |
|------------------------------------------------------------------|-----------------|
| Color                                                            | gray (RAL 7042) |
| Flammability rating according to UL 94                           | V0              |
| Insulating material group                                        | I               |
| Insulating material                                              | PA              |
| Static insulating material application in cold                   | -60 °C          |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26           | HL 1 - HL 3     |
| Surface flammability NFPA 130 (ASTM E 162)                       | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)          | passed          |
| Smoke gas toxicity NFPA 130 (SMP 800C)                           | passed          |

## Electrical tests

### Surge voltage test

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Temperature-rise test

|                                                |                                |
|------------------------------------------------|--------------------------------|
| Requirement temperature-rise test              | Increase in temperature ≤ 45 K |
| Result                                         | Test passed                    |
| Short-time withstand current 4 mm <sup>2</sup> | 0.48 kA                        |
| Short-time withstand current 6 mm <sup>2</sup> | 0.72 kA                        |
| Result                                         | Test passed                    |

### Power-frequency withstand voltage

|                       |      |
|-----------------------|------|
| Test voltage setpoint | 2 kV |
|-----------------------|------|

# UTTB 4 - Double-level terminal block



3044814

<https://www.phoenixcontact.com/gb/products/3044814>

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 35       |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                                |                               |
|--------------------------------|-------------------------------|
| Rotation speed                 | 10 rpm                        |
| Revolutions                    | 135                           |
| Conductor cross section/weight | 0.14 mm <sup>2</sup> / 0.2 kg |
|                                | 4 mm <sup>2</sup> / 0.9 kg    |
|                                | 6 mm <sup>2</sup> / 1.4 kg    |
| Result                         | Test passed                   |

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# UTTB 4 - Double-level terminal block

3044814

<https://www.phoenixcontact.com/gb/products/3044814>

## Drawings

Circuit diagram



# UTTB 4 - Double-level terminal block



3044814

<https://www.phoenixcontact.com/gb/products/3044814>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/3044814>

### DNV

Approval ID: TAE00001S9



### CSA

Approval ID: 13631

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 300 V                 | 30 A                  | 26 - 10           | -                           |
| Use group C |                       |                       |                   |                             |
|             | 300 V                 | 30 A                  | 26 - 10           | -                           |
| Use group D |                       |                       |                   |                             |
|             | 600 V                 | 5 A                   | 26 - 10           | -                           |



### cULus Recognized

Approval ID: E60425



### cULus Recognized

Approval ID: E60425



### ATEX

Approval ID: KEMA06ATEX0017U



### cUL Recognized

Approval ID: E192998

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 300 V                 | 30 A                  | 26 - 10           | -                           |
| Use group C |                       |                       |                   |                             |
|             | 300 V                 | 30 A                  | 26 - 10           | -                           |



### IECEx

Approval ID: IECEx KEM 06.0013U



### UL Recognized

Approval ID: E192998

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|--|-----------------------|-----------------------|-------------------|-----------------------------|

# UTTB 4 - Double-level terminal block



3044814

<https://www.phoenixcontact.com/gb/products/3044814>

|             |       |      |         |   |
|-------------|-------|------|---------|---|
| Use group B |       |      |         |   |
|             | 300 V | 30 A | 26 - 10 | - |
| Use group C |       |      |         |   |
|             | 300 V | 30 A | 26 - 10 | - |



**CCC**

Approval ID: 2020322313000622



**UKCA-EX**

Approval ID: DEKRA 21UKEX0305U



# UTTB 4 - Double-level terminal block



3044814

<https://www.phoenixcontact.com/gb/products/3044814>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250102 |
| ECLASS-15.0 | 27250102 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UTTB 4 - Double-level terminal block



3044814

<https://www.phoenixcontact.com/gb/products/3044814>

## Environmental product compliance

### EU RoHS

|                                         |      |
|-----------------------------------------|------|
| Fulfills EU RoHS substance requirements | Yes  |
| Exemption                               | 6(c) |

### China RoHS

|                                        |                                                                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-50                                                                                                                                                                                                                           |
|                                        | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | 44a544a9-d2ee-49aa-9473-ba64016995dc |

### EF3.0 Climate Change

|         |              |
|---------|--------------|
| CO2e kg | 0.08 kg CO2e |
|---------|--------------|

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
Halesfield 13, Telford  
Shropshire, TF7 4PG  
01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)