



084Z8047 🗷

Temperature sensor, MBT 5250, 150 mm, G,1/2

Temperature range [°C]: -50 - 200, Sensor element type: Pt, Sensor elem. resistance [Ohm]: 100, Protection tube material: AISI 316 TI, Electrical connection: Angular connector, Electrical connection size: Pg 13.5

PRODUCT DETAILS

Gross weight	0.22 Kilogram
Net weight	0.171 Kilogram
Volume	0.594 Liter
EAN	5702423084104
Туре	MBT 5250
Product group	Sensors
Product Name Description	Temperature sensor
Ambient temperature max. [°C]	125 ℃
Ambient temperature max. [°F]	257 °F
CE evaluated	Yes
China RoHS compliance	Out of scope
Connection material	Stainless steel
Connection standard	ISO 228
Connection type	G
Contains batteries	No
EEE category	5 small equipment (any external
	dimension < 50 cm)
Electrical conn. Male/Female	Male and Female
Electrical connection	Angular connector
Electrical connection size	Pg 13.5
Electrical connection standard	EN 175301-803-A
Enclosure rating IP	IP65
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
In scope of WEEE	Yes
Insertion length [in]	5.9 in
Insertion length [mm]	150 mm
Insertion type	Fixed
Number of terminals [pcs]	3 pc
Output signal	Ohm
Packing format	Multi pack
Process connection Male/Female	Male
Process connection material	Stainless steel
Process connection size	1/2
Process connection standard	ISO 228-1-A
Process connection type	G
Protection tube diameter [in]	0.315 in
Protection tube diameter [mm]	8 mm

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS

Protection tube material	AISI 316 TI	
Quantity per packing format	12 pc	
REACH Candidate List substances	Lead (CAS no. 7439-92-1)	
SCIP dossier no.	1741c763-	
	fa54-4cb9-973c-52e51e4079b9	
Sensor elem. resistance [Ohm]	100 Ohm	
Sensor element [pc]	1 pc	
Sensor element standard	EN 60751	
Sensor element tolerance	Class B	
Sensor element type	Pt	
Sensor Insert	Exchangeable	
Temperature range [°C] [max]	200 ℃	
Temperature range [°C] [min]	-50 °C	
Temperature range [°F] [max]	392 °F	
Temperature range [°F] [min]	-58 °F	
Type designation	MBT 5250-0000-150-320	
Wires [pcs]	2 pc	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🗷

Accessories



084Z2441 🗷

Sensor pocket, MBT 120

Protection tube diameter [mm]: 11, Insertion length [mm]: 150, Process connection type: G, 1/2, Temperature range [°C]: -50 - 200, Protection tube material: AISI 316 Ti, Used for product: MBT 5250