



PYF14A-N

Socket, DIN rail/surface mounting, 14-pin, screw terminals (IEC/VDE)

Specifications

Applicable product family	MY2K, MY4, MY4 without CR, MY4-GS
Mounting method	DIN rail/screw
Terminal type	Screw
Product Width (unpacked)	29.5 mm
Product Height (unpacked)	67 mm
Product Depth (unpacked)	30 mm
Color	Beige
Release Lever included	✘

Fits to



MY4-GS-R AC110/120

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 100/110 VAC



MY4-GS-R AC12

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VAC



MY4-GS-R AC220/240

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 220/240 VAC



MY4-GS-R AC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VAC



MY4-GS-R AC48

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VAC



MY4-GS-R DC100/110

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 100/110 VDC



MY4-GS-R DC12

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VDC



MY4-GS-R DC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VDC

**MY4-GS-R DC48**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VDC

**MY4IN-CR-GS-R AC110/120**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 110/120 VAC

**MY4IN-CR-GS-R AC220/240**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 220/240 VAC

**MY4IN-D2-GS-R DC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 24 VDC

**MY4IN-GS-R AC110/120**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

**MY4IN-GS-R AC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 12 VAC

**MY4IN-GS-R AC200/220**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 200/220 VAC

**MY4IN-GS-R AC220/240**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 220/240 VAC

**MY4IN-GS-R AC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VAC

**MY4IN-GS-R AC48**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 48 VAC

**MY4IN-GS-R DC100/110**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 100/110 VDC

**MY4IN-GS-R DC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 12 VDC

**MY4IN-GS-R DC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VDC

**MY4IN-GS-R DC48**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 48 VDC

Accessories



PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length



PFP-100N2

DIN-rail mounting track, 35x16mm, 1m length



PFP-50N

Din rail track, 500 mm



PFP-M

End plate



PYC-A1

Retaining clips for LY/MY relay & PTF/PYF_E/N socket



XW5Z-EP6

End bracket for terminal blocks, 6 mm width

Downloads



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**MY(S) Miniature Power
Relays
Datasheet**

EN PDF 9.24 MB