



## K8AK-LS1 24VAC/DC

Monitoring relay 22.5 mm wide, Conductive level control for liquid, 10k to 100k Ohm, One SPDT, 24VAC/DC

# Specifications

Application	Ordinary purified water, Sewage water
Functions	Conductive level control
Cable length	100 m
Installation type	DIN rail
Terminal type	Screw
Size	22.5 mm
Supply voltage AC	20.4-26.4 V
Supply voltage DC	20.4-26.4 V
Output type	Relay
Contact description	SPDT
Body color	Black
Number of inputs for electrodes	3

# Accessories



**BF-1**

Electrode holder, 1-pole electrode, standard type (150°C), liquid with low specific resistance



**BF-5**

Electrode holder, 5 way, standard type (150°C)



**BS-1**

Electrode holder, 1-pol electrode, for high pressure or high temperature applications (250°C), 1.96Mpa



**F03-11 PROTECTIVE COVER FOR BF**

Protective cover for electrode holders PS or BF series)



**F03-12 FRAME FOR  
FIXATION**

PS Electrode Holder Mounting Plate



**F03-14 1P SEPARATOR**

Electrode separator, 1 electrode, ceramic, 250 °C max, 15 g



**F03-14 3P SEPARATOR**

Electrode separator, 3 electrodes, ceramic, 250 °C max, 30 g



**F03-14 5P SEPARATOR**

Electrode separator, 5 electrodes, ceramic, 250 °C max, 30 g

**PH-2 HAIPREN CODE 20M**

Underwater Electrode, Hypalon cable, double pole, 20 m length



**PS-31 SUS304 1000MM**

Electrode set, holder & electrodes, 1 m length, 4 mm diameter, non-extendable



**PS-31 SUS304 300MM**

Electrode set, holder & electrodes, 0.3 m length, 4 mm diameter, non-extendable



**PS-3S**

Electrode holder, 3 way



**PS-4S**

Electrode holder, 4 way



**PS-5S**

Electrode holder, 5 way

CAD Library



## EAC Mark removal Discontinuation Notice

EN PDF 221 KB



## K8AK-LS Conductive Level Controller Datasheet

EN PDF 2.36 MB



## Solution case study No.8 Environment resistance Brochure

EN PDF 623 KB