



PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

Specifications

Applicable product family	H3YN, MY2K, MY4, MY4-GS
Mounting method	DIN rail/screw
Terminal type	Screw
Product Width (unpacked)	29.5 mm
Product Height (unpacked)	72 mm
Product Depth (unpacked)	31 mm
Color	Black
Hold down clip included	×
Release Lever included	×
Applicable ferrules	Forked terminals

Fits to



MY4-GS-R AC110/120

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical
indicator, 100/110 VAC



MY4-GS-R AC12

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical
indicator, 12 VAC



MY4-GS-R AC220/240

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical
indicator, 220/240 VAC



MY4-GS-R AC24

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical
indicator, 24 VAC



MY4-GS-R AC48

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VAC



MY4-GS-R DC100/110

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 100/110 VDC



MY4-GS-R DC12

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VDC



MY4-GS-R DC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VDC



MY4-GS-R DC48

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VDC



MY4H 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed



MY4H 12VDC

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed



MY4H 24VAC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 24 VAC



MY4H 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, hermetically-sealed



MY4IN-CR-GS-R AC110/120

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 110/120 VAC



MY4IN-CR-GS-R AC220/240

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 220/240 VAC



MY4IN-D2-GS-R DC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 24 VDC



MY4IN-GS-R AC110/120

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 110/120 VAC



MY4IN-GS-R AC12

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 12 VAC



MY4IN-GS-R AC200/220

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 200/220 VAC



MY4IN-GS-R AC220/240

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 220/240 VAC



MY4IN-GS-R AC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VAC



MY4IN-GS-R AC48

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 48 VAC



MY4IN-GS-R DC100/110

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 100/110 VDC



MY4IN-GS-R DC12

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 12 VDC



MY4IN-GS-R DC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VDC



MY4IN-GS-R DC48

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 48 VDC



MY4IN1 100/110VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, lockable push to test button, label facility, 100/110 VDC



MY4IN1 12VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, lockable push to test button, label facility, 12 VDC



MY4IN1 48VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, lockable push to test button, label facility, 48 VDC



MY4IN1 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, label facility, 24 VDC



MY4Z 110/120VAC (S)

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 100/120 VAC



MY4Z 220/240VAC (S)

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 220/240 VAC



MY4Z 24VDC (S)

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 24 VDC



MY4ZH 100/110VAC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts, 110 VAC



MY4ZH 24VDC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts



MY4ZIN 220/240VAC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, test button, 220/240 VDC



MY4ZIN 24VAC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, test button, 24 VAC



MY4ZIN 24VDC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, test button, 24 VDC



MY4ZIN-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 24 VDC



MY4ZIN1 24VDC (S)

Relay, plug-in, 4PDT (bifurcated), reverse coil polarity, 3 A, mech. + LED indicator, test button, 24 VDC



MY4ZN 110/120VAC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 110/120 VAC



MY4ZN 220/240VAC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 220/240 VAC



MY4ZN 24VAC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 24 VAC



MY4ZN 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 24 VDC



MY4ZN 48/50VAC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 48/50 VAC



MY4ZN-CR 110/120VAC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, RC circuit, 110/120 VAC



MY4ZN-CR 220/240VAC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, RC circuit, 220/240 VAC



MY4ZN-D2 100/110VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor label facility, 100/110 VDC



MY4ZN-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor label facility, 24 VDC



MY4ZN-D2 48VDC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, diode, 48 VDC



MY4ZN1-D2 24VDC (S)

Relay, plug-in, 4PDT (bifurcated), reverse coil polarity, 3 A, mech. + LED indicator, diode, 24 VDC



MYQ4 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 110/120 VAC



MYQ4 220/240VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 220/240 VAC



MYQ4 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 24 VDC



MYQ4N 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 110/120 VAC



MYQ4N 220/240VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 220/240 VAC



MYQ4N 24VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 24 VAC



MYQ4N 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 24 VDC



MYQ4Z 200/220VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, , bifurcated contacts

Accessories



PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length



PFP-100N2

DIN-rail mounting track, 35x16mm, 1m length



PFP-50N

Din rail track, 500 mm



PFP-M

End plate



PYC-A1

Retaining clips for LY/MY relay & PTF/PYF_E/N socket



XW5Z-EP6

End bracket for terminal blocks, 6 mm width



Y92F-78

Flush panel mounting adapter for H3Y(N) timer



Y92H-3

Clips for H3Y(N) timer & PYF socket

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



MY(S) Miniature Power Relays Datasheet

EN PDF 9.24 MB