



 PRODUCT-DETAILS

MO325-9

MO325-9 Manual Motor Starter Magnetic Only 9 A



General Information

Extended Product Type	MO325-9
Product ID	1SAM160000R1010
EAN	4013614302060
Catalog Description	MO325-9 Manual Motor Starter Magnetic Only 9 A

Long Description	<p>The MO325-9 manual motor starter magnetic only is a 54 mm width device with a rated operational current of $I_e = 9.0$ A. This device is used to manually switch on and off motors and to protect them reliably and without the need for a fuse from short-circuits. The manual motor starter magnetic only offers a rated service short-circuit breaking capacity $I_{cs} = 100$ kA at 400 VAC. Further features are the build-in disconnect function, trip-free mechanism and a rotary handle with a clear switch position indication. The manual motor starter magnetic only is suitable for three- and single-phase applications. Auxiliary contacts, signalling contacts, undervoltage releases, shunt trips, 3-phase bus bars, power in-feed blocks are available as accessory.</p>
------------------	--

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362010
Replacement Product ID (NEW)	1SAM360000R1010

Popular Downloads

Data Sheet, Technical Information	2CDC131047D0201
Instructions and Manuals	2CDC131089M6801

Dimensions

Product Net Width	54 mm
Product Net Height	87.5 mm
Product Net Depth / Length	75.5 mm
Product Net Weight	0.34 kg

Technical

Rated Service Short-Circuit Breaking Capacity (I_{cs})	(230 V AC) 100 kA (400 V AC) 100 kA (440 V AC) 50 kA (500 V AC) 30 kA (690 V AC) 5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(230 V AC) 100 kA (400 V AC) 100 kA (440 V AC) 50 kA (500 V AC) 30 kA (690 V AC) 5 kA
Rated Instantaneous Short-Circuit Current Setting (I_i)	135 A
Setting Range	None
Rated Operational Power AC-3 (P_e)	(400 V) Three Phase 4 kW
Rated Operational Voltage	Main Circuit 690 V AC Main Circuit 440 V DC
Rated Operational Current (I_e)	9 A
Rated Operational Current AC-3 (I_e)	9 A
Rated Frequency (f)	Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 6 kV
Rated Insulation Voltage (U_i)	690 V
Power Loss	at Rated Operating Conditions per Pole 1.8 W
Number of Poles	3P
Conventional Free-air Thermal Current (I_{th})	Main Circuit 9 A
Degree of Protection	Housing IP20 Main Circuit Terminals IP20
Pollution Degree	3
Electrical Durability	50000 cycle
Mechanical Durability	Nr. Operations 100000 cycle
Terminal Type	Screw Terminals
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 0.75 ... 4 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 4 mm ²

	Flexible 1/2x 1 ... 6 mm ² Rigid 1/2x 1 ... 6 mm ²
Tightening Torque	Main Circuit 1.4 N·m
Wire Stripping Length	Main Circuit 10 mm
Recommended Screw Driver	M3.5 Poqidriv 2
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Actuator Type	Rotary Handle
Contact Position Indication	ON / OFF
Standards	CSA 22.2 No. 14 IEC/EN 60947-1 IEC/EN 60947-2 IEC/EN 60947-4-1 UL 508
Remarks	For overload protection of the motors, an appropriate thermal or electronic overload relays must be used

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Horsepower Rating UL/CSA	(220 ... 240 V AC) Three Phase 2.5 Hp (440 ... 480 V AC) Three Phase 5 Hp (550 ... 600 V AC) Three Phase 7.5 Hp
Connecting Capacity Main Circuit UL/CSA	Flexible 1/2x 14-8 AWG Stranded 1/2x 14-8 AWG
Tightening Torque UL/CSA	Main Circuit 14 in-lb

Environmental

Ambient Air Temperature	Around the Enclosure 0 ... +40 °C Operation -25 ... +50 °C Storage -50 ... +80 °C
Ambient Air Temperature Compensation	No
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
Resistance to Vibrations	5g 10 ... 150 Hz

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SAA960005-4502
RoHS Declaration	1SAA963006-4502
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006539
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	1SAA918000-2003
CCC Certificate	2024010307659819
CQC Certificate	CQC2017010307033534
cUL Certificate	cUL_E137861
cULus Certificate	E137861
Declaration of Conformity - CCC	2020980307003580
Declaration of Conformity - CE	1SAD101100-3413
Declaration of Conformity - UKCA	1SAD201100-3413
DNV Certificate	1SAA918000-0306
GL Certificate	1SAA918000-0403
LR Certificate	1SAA918000-0504
RINA Certificate	1SAA918000-0804
RMRS Certificate	1SAA918000-0704
UL Certificate	UL_E137861

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	92 mm
Package Level 1 Depth / Length	58 mm
Package Level 1 Height	78 mm
Package Level 1 Gross Weight	0.37 kg
Package Level 1 EAN	4013614302060
Package Level 2 Units	carton 24 piece
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	8.9 kg
Package Level 2 EAN	4013614495021

External Classifications and Standards

Object Classification Code	F
ETIM 9	EC000074 - Motor protection circuit-breaker
ETIM 10	EC000074 - Motor protection circuit-breaker
eClass	V11.0 : 27370401
UNSPSC	39121521
IDEA Granular Category Code (IGCC)	4731 >> Manual Starters

Categories

Low Voltage Products and Systems → Circuit Breakers → Manual Motor Starters

Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters

