



175G5217 

MCD202075T4CV3
MCD202075T4CV3

MCD202075T4CV3
VLT® Compact Starter MCD 202
75 kW 140A:4-6: 594
Three phase, 200-440 VAC
Control voltage: 110/240 VAC or 440 VAC
(C) C-Frame

Model code: MCD202075T4CV3

VLT® Compact Starter MCD 200 from Danfoss includes two families of soft starters in the power range 7.5–110 kW. The series offers easy DIN rail mounting for sizes up to 30 kW, 2-wire or 3-wire start/stop control and excellent starting duty (4 x Ie for 6 seconds). Heavy starting rating at 4x Ie for 20 seconds. Compatible with grounded delta power systems.

PRODUCT DETAILS

Gross weight		7.6 kg
Net weight		6.8 kg
Volume		25.792 l
EAN		5702427098572
VLT® COMPACT STARTER MCD200 SERIES		
Product View (Switch)	GLBL	Global (Standard)
Product Group	MCD	VLT® Soft Starter MCD
MCD Series	202	202
Power Rating	075	75 kW 140A:4-6: 594
Phase	T	Three phase
Mains Voltage	4	200-440 VAC
Control Supply Voltage	CV3	110/240 VAC or 440 VAC
Frame Size	C	(C) C-Frame
Typecode Part 1		MCD202075T4CV3
Product Catalog	NO_VIEW	NO VIEW
Modelcode01		MCD202075T4CV3
ECCN EU		Y901
ECCN US		EAR99
Calculated Gross Weight [kg]		7.3
Calculated Net Weight [kg]		6.5
Plant from Orderline		B401
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**175G9009** [↗](#)**USB Module**

USB module for MCD 200 and MCD 500

**175G9007** [↗](#)**Finger Guard Kit, IP20****175G9004** [↗](#)**Remote Operator kit MCD200**

Remote control unit for MCD 200 soft starter.

**175G9002** [↗](#)**Devicenet module, MCD200, MCD500****175G9001** [↗](#)**Profibus Module, MCD200, MCD500**

Profibus option for MCD 200 and MCD 500

**175G9000** [↗](#)**Modbus RTU Module, MCD200, MCD500**

Modbus RTU module (RS485) for MCD 200 and MCD 500

**175G9905** [↗](#)**Profinet module, MCD200, MCD500**

ProfiNet module

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.