



E3FB-LP21

Photoelectric sensor, M18 threaded barrel, metal, red LED, background suppression, 100 mm, PNP, Light-ON/Dark-ON, M12 connector

Specifications

Shape	Cylindrical axial
Sensing method	Background suppression
Sensing distance	100 mm
Setting method	Fixed
Connection method	Connector M12
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	0.5 ms
Material housing	Brass, nickel plated
Thread size	M18
Product Length (unpacked)	48 mm
Type of light	Polarity free red light
Power supply voltage	10-30 V
Degree of protection (IP)	IP67/IP69K

Accessories



E39-L183

M18 L-type mounting bracket, stainless steel (SUS304)

Related products



M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

Downloads

CAD Library



E3FA Cylindrical Photoelectric Sensors Brochure

EN PDF 9.01 MB



E3FA/E3RA/E3FB/E3RB Photoelectric Sensors Datasheet

EN PDF 6.32 MB



E3FB-_____ Instruction Manual

EN PDF 351 KB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 12 August, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU