



## NX-OD6256-5











32 Digital Outputs, Standard speed, PNP 24 VDC, 0.5 A/point, 4 A/NX Unit, MIL40 connector (not included), 30 mm wide

# Specifications

I/O system	NX I/O Bus
Type of module	Digital I/O
Number of digital inputs	0
Digital input type	None
OFF/ON delay	0.5-1.0 ms
Number of digital outputs	32
Digital output type	PNP
Permitted voltage at output	20.4-28.8 V
Output current	0.5 A
Short-circuit protected outputs	✓
Connection method	1-wire
Signal processing	Free running, Standard speed, Synchronous
IO-Link master	✗
I/O connection type	MIL (plug not included)
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Communication port(s)	None
Number of IOV (V+) terminals	4
Number of IOG (V-) terminals	4
Number of COM terminals	0
Degree of protection (IP)	IP20

Product Height (unpacked)	100 mm
Product Width (unpacked)	30 mm
Product Depth (unpacked)	89.52 mm
Product Weight (unpacked)	95 g

## Accessories

	<b>G70A-ZOC16-4 DC24</b>	Output Terminal Block for Relay or SSR, 16-point, for PNP output units
	<b>G70V-SOC16P-1</b>	Relay terminal, PLC Output, 16 channels, PNP, Push-in terminals
	<b>P2RV-4-100C</b>	G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 1 m
	<b>P2RV-4-200C</b>	G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 2 m
	<b>P2RV-4-300C</b>	G2RV interface cable for use between CJ1W-OD232/OD262 and 4 P2RV-8-O-F modules, 3 m
	<b>XW2D-20G6</b>	General-purpose I/O terminal block, MIL20 socket, M3 captive screws, 20 points
	<b>XW2D-40G6</b>	General-purpose I/O terminal block, MIL40 socket, M3 captive screws, 40 points
	<b>XW2K-40G-O32C</b>	PLC interface wiring system with push-in plus technology and power supply terminal, 40 points MIL connector, Input/Output, 0.5 A, NPN/PNP, 30 VDC, DIN rail horizontal and vertical mounting
	<b>XW2Z-0030FF-L</b>	I/O connection cable, unshielded, MIL40 to MIL40, 0.3 m
	<b>XW2Z-0050FF-L</b>	I/O connection cable, unshielded, MIL40 to MIL40, 0.5 m



**XW2Z-0100FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 1 m



**XW2Z-0100FH-L01**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 1 m, cross-wired



**XW2Z-0100FH-L02**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 1 m



**XW2Z-0100FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 1 m



**XW2Z-0150FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 1.5 m



**XW2Z-0150FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 1.5 m



**XW2Z-0200FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 2 m



**XW2Z-0200FH-L01**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 2 m, cross-wired



**XW2Z-0200FH-L02**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 2 m



**XW2Z-0200FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 2 m



**XW2Z-0300FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 3 m



**XW2Z-0300FH-L02**

I/O connection cable, unshielded, MIL40 to 2 x MIL20, 3 m



**XW2Z-0300FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 3 m



**XW2Z-0500FF-L**

I/O connection cable, unshielded, MIL40 to MIL40, 5 m



**XW2Z-0500FN-L**

I/O connection cable, unshielded, MIL40 to open ends, 5 m



**XW2Z-100K**

I/O connection cable, MIL40 to MIL40, 1 m



**XW2Z-100N**

I/O connection cable, MIL40 to 2 x MIL20, 1 m, cross-wired



**XW2Z-150K**

I/O connection cable, MIL40 to MIL40, 1.5 m



**XW2Z-200K**

I/O connection cable, MIL40 to MIL40, 2 m



**XW2Z-200N**

I/O connection cable, MIL40 to 2 x MIL20, 2 m, cross-wired



**XW2Z-300K**

I/O connection cable, MIL40 to MIL40, 3 m



**XW2Z-500K**

I/O connection cable, MIL40 to MIL40, 5 m



**XW2Z-500N**

I/O connection cable, MIL40 to 2 x MIL20, 5 m, cross-wired



**XW2Z-RO100-75-D1**

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 1 m



**XW2Z-RO200-175-D1**

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 2.0 m and 1.75 m



**XW2Z-RO75-50-D1**

I/O connection cable, with shield connection, MIL40 to 2 x MIL20 for G70V-ZOC16-3, 0.75 m

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### IO-Link Series Brochure

EN PDF 7.5 MB



### Machine Safety Solution Brochure

EN PDF 2.86 MB



### NX-HAD Brochure

EN PDF 1.22 MB



### NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.28 MB



### NX-series Reference Manual

EN PDF 1.45 MB



### NX-series Digital I/O Unit - NX-ID/IA/OD/OC/MD Datasheet

EN PDF 4.49 MB



### NX-series Digital I/O Units Users Manual

EN PDF 11.5 MB



### NX-series I/O system Brochure

EN PDF 8.37 MB



### Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



### Sysmac Catalogue

EN PDF 43.5 MB



### Sysmac: A Fully Integrated Platform Brochure

EN PDF 19.1 MB