

SIMATIC IFP 1500 V2 ext. hygienic, IP69, stainless steel, 15" multi-touch display (16:9) with 1920x1080 pixel resolution, built-in unit for 24 V DC, display port interface, can be placed up to 100 m away HDBaseT, USB on the rear side, blue FDA compliant gasket, increased impact protection with splinter protection display front according to directives EN 1672-2, FDA 21 CFR 177.2006 hygienic design



General information	
Product type designation	IFP1500 V2 ext. hyg.
Short designation	Flat Panel 15" multi-touch ext. hygienic
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	15.6 in; 15"
Screen diagonal [cm]	40 cm
Display width	344.2 mm
Display height	193.5 mm
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Viewing angle	178° x 178°
Resolution (pixels)	
<ul style="list-style-type: none"> Image resolution 	1 920 x 1 080
<ul style="list-style-type: none"> Pixel size, horizontal 	0.17925 mm
<ul style="list-style-type: none"> Pixel size, vertical 	0.17925 mm
General features	
<ul style="list-style-type: none"> Brightness/contrast 	400 cd/m ² / 700:1
<ul style="list-style-type: none"> non-reflective and tempered mineral glass screen 	No; reinforced pane with shatter protection film
<ul style="list-style-type: none"> Detachable from computer unit 	100 m; HDBaseT protocol
Backlighting	
<ul style="list-style-type: none"> Type of backlighting 	LED
<ul style="list-style-type: none"> MTBF backlighting (at 25 °C) 	50 000 h; At 25°C
<ul style="list-style-type: none"> Backlight dimmable 	Yes; 0-100 %
Control elements	
Control elements	multi-touch screen
Input device	
<ul style="list-style-type: none"> Integrated mouse cursor control 	Yes; Also externally via USB
Touch operation	
<ul style="list-style-type: none"> Design as touch screen 	Yes; Projective-capacitive
<ul style="list-style-type: none"> Design as multi-touch screen 	Yes; Projective-capacitive
<ul style="list-style-type: none"> Monitor keyboard 	Yes; If supported by operating system
Installation type/mounting	
Design	Built-in unit
Front mounting	Yes
VESA mounting	Yes; VESA 100 x 100 integrated
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
Built-in unit	Yes; Portrait mode possible
maximum permitted forward tilt angle from vertical	35°

maximum permitted backward tilt angle from vertical	35°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; PELV / SELV floating
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	1 A
Current consumption, max.	1.3 A
Starting current inrush I _t	0.5 A ² ·s
Power loss	
Power loss, typ.	24 W
Power loss, max.	30 W
Interfaces	
Number of USB interfaces	2; USB 2.0 type A
USB on the rear	Yes; 2x onboard
Connection for keyboard/mouse	USB
Video interfaces	
• DisplayPort	Yes; Display port V1.2
Touch interfaces	
• USB	Yes; (device)
Degree and class of protection	
IP (at the front)	IP66K, IP69
IP (rear)	IP20
NEMA (front)	
• Enclosure Type 4x at the front	Yes
• Enclosure Type 12 at the front	Yes
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	No; in preparation
CCC	No; in preparation
EMC	CE, EN 55011, EN 61000-6-4, EN 61000-6-2
Use in hazardous areas	
• ATEX Zone 2	Yes
• ATEX Zone 22	Yes
• IECEx Zone 2	Yes
• IECEx Zone 22	Yes
• cULus Class I Zone 2, Division 2	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
Relative humidity	
• Operation, max.	90 %; no condensation
Vibrations	
• Vibration load in operation	10 m/s ²
• Vibration load during transport/storage	10 m/s ²
Shock testing	
• Shock load during operation	150 m/s ²
• shock acceleration during storage/transport	250 m/s ²
Mechanics/material	
Enclosure material (front)	

- Plastic
- Stainless steel

Yes; shatter protection film
Yes

Enclosure material (rear) stainless steel, aluminum

Dimensions

Width of the housing front 411.8 mm
 Height of housing front 272.2 mm
 Mounting cutout, width 382 mm; Tolerance: +1 mm
 Mounting cutout, height 241 mm; Tolerance: +1 mm
 Overall depth 67.7 mm

Weights

Weight (without packaging) 4.7 kg

Classifications

	Version	Classification
eClass	14	19-20-02-01
eClass	12	19-20-02-01
eClass	9.1	19-20-02-01
eClass	9	19-20-02-01
eClass	8	19-20-02-01
eClass	7.1	19-20-02-01
eClass	6	19-20-02-01
ETIM	9	EC001428
ETIM	8	EC001428
ETIM	7	EC001428

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)



[Miscellaneous](#)

[KC](#)



EMV

For use in hazardous locations

other

[KC](#)

[CCC-Ex](#)



Food, Pharmaceutical, Medical

[Miscellaneous](#)

[Special Test Certificate](#)

last modified:

7/1/2025