

**018F6252****Solenoid coil, BF240AS, Cable, 1 m, Supply voltage [V] AC: 240, Multi pack**

Electrical connection: Cable, Supply voltage [V] AC: 240, Frequency [Hz]: 50 Hz, Enclosure rating IP: IP67

PRODUCT DETAILS

Gross weight	0.358 Kilogram
Net weight	0.305 Kilogram
Volume	0.878 Liter
EAN	5702428024839
Type	BF240AS
Product group	Solenoid valves
Product Name Description	Solenoid coil
Actuator size	13.5 mm
Ambient temperature range [°C] [max]	80 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	175 °F
Ambient temperature range [°F] [min]	-40 °F
Approval	LLC CDC TYSK
Cable diameter [mm]	6.6 mm
Cable length [in]	40 in
Cable length [m]	1 m
China RoHS compliance	Out of scope
Coil connection	Cable
Coil design standard	VDE 0580
Coil fastening	Clip-on
Coil winding insulation class	Class H to IEC 85
Colour	Blue
Compliance	EN 60730-1
Conductor area [mm²]	3 x 0.75 mm ²
Contains batteries	No
Duty rating	Continuous
EEE category	5 small equipment (any external dimension < 50 cm)
Electrical connection	Cable
Electrical connector	3 core cable
Enclosure rating IP	IP67
EU RoHS compliance	Out of scope
Frequency [Hz]	50 Hz
Identical product	018F8202
In scope of WEEE	Yes

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

Packing format	Multi pack
Parts Program name	EV210B EV212B EV220B 15 - 50 EV220B 6 - 22 EV220B 65 - 100 EV222B EV224B EV227B EV250B EV251B
Power consumption 50Hz [VA]	19 VA
Power consumption [W] 50Hz	11 W
Product accessories	Solenoid coil accessories
Quantity per packing format	24 pc
REACH Candidate List substances	No
Rel. Humidity [% RH] [max]	100 %
Rel. Humidity [% RH] [min]	0 %
Serviceable	No
Spare part number	018F6252
Supply voltage 50Hz Max [V]	240 V
Supply voltage [V] AC	240 V
Type designation	BF240AS

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

We're sorry, but the requested information is currently unavailable.

This may be because accessories for this product are not available or the data is incomplete.

For the latest and most accurate information, please visit store.danfoss.com.

Thank you for your understanding.

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.