

**061B100866****Pressure switch, MBC 5100**

Regulation range [bar] Pe: 1 - 10, Reset function: Auto, Pressure connection type: G, Pressure connection size: 1/4, Enclosure rating IP: IP65, Max. Working Pressure [bar]: 150

**PRODUCT DETAILS**

<b>Gross weight</b>	0.294 Kilogram
<b>Net weight</b>	0.24 Kilogram
<b>Volume</b>	0.647 Liter
<b>EAN</b>	5702423218653
<b>Type</b>	MBC 5100
<b>Product group</b>	Switches and thermostats
<b>Product Name Description</b>	Pressure switch
<b>Ambient temperature range [°C] [max]</b>	85 °C
<b>Ambient temperature range [°C] [min]</b>	-10 °C
<b>Ambient temperature range [°F] [max]</b>	185 °F
<b>Ambient temperature range [°F] [min]</b>	14 °F
<b>Approval</b>	ABS BV CCC CCS CE CMIM DNV EAC GL KRS LLC CDC EURO-TYSK LR LVD NKK RINA RMRS RoHS RoHS China TYSK
<b>Burst pressure [bar]</b>	300 bar
<b>CE evaluated</b>	Yes
<b>China RoHS compliance</b>	Yes
<b>Contact function</b>	SPDT
<b>Contact rating</b>	AC15=0.5 A, 250 V DC13=12 W, 125 V

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Pressure switch, MBC 5100

## PRODUCT DETAILS

Contains batteries	No
Diff.@Max. range setting [bar]	2.5 bar
Diff.@Min. range setting [bar]	1 bar
Electrical conn. Male/Female	Female
Electrical connection	DIN-plug
Electrical connection size	Pg 11
Electrical connection standard	EN 175301-803-A
Electrical spec. standard	EN 60947-5
Enclosure rating IP	IP65
EU RoHS compliance	Out of scope
Max. test pressure [bar] Pe	150 bar
Max. test pressure [psig]	2176 psig
Max. Working Pressure [bar]	150 bar
Max. Working Pressure [psig]	2175 psig
Other RoHS documentation	Saudi Arabia RoHS
Packing format	Multi pack
Pressure connection size	1/4
Pressure connection standard	ISO 228-1
Pressure connection type	G
Pressure Male/Female	Female
Pressure sensing element	Diaphragm
Product accessories	Switches accessories
Product description	Pressure Switch
Quantity per packing format	32 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Regulation range [bar] Pe [max]	10 bar
Regulation range [bar] Pe [min]	1 bar
Regulation range [MPa] Pe [max]	1 MPa
Regulation range [MPa] Pe [min]	0.1 MPa
Reset function	Auto
SCIP dossier no.	69958bd3-3b22-42dc-aa8a-888e92c5e7e8
SCIP dossier product name	MBC 5100 5000 Pressure Switch
Serviceable	No
Specification key	2431-1CB04

[For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store](#)

## Accessories

Image  
coming  
soon

**061B400166****Test valves accessories, Damping device**

Damping device, Used for product: MBC, Packing format: Multi pack, Quantity per packing format: 70

[For more information, please use this link to visit the product page on Danfoss Product Store](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



---

Accessories

---

Image  
coming  
soon

**061B400266** [🔗](#)

**Test valves accessories, Damping device**

Damping device, Used for product: MBC, Packing format: Multi pack, Quantity per packing format: 64

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.