

MM-EMLF (EX24)R C1 WH/BK - Label, highly flexible



0803940

<https://www.phoenixcontact.com/gb/products/0803940>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Label, highly flexible, Roll, white/black, unmarked, can be labeled with: THERMOFOX, THERMOMARK GO, THERMOMARK GO.K, mounting type: adhesive, roll length: 8 m, text field height: 22 mm, text field width: 8000 mm

Your advantages

- High-quality and solvent-resistant marking solution for industrial applications that is created by means of thermal transfer printing
- The self-adhesive material in continuous format is particularly suitable for the professional and permanent marking of various components and equipment in control cabinet, controller, and systems manufacturing
- Thanks to the continuous format, a label of the appropriate length can be created flexibly for the relevant application
- Easy and efficient material cartridge system: Includes both the material to be printed and the corresponding ink ribbon
- The material is cUL certified

Commercial data

Item number	0803940
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG241E
Product key	BG241E
GTIN	4055626212197
Weight per piece (including packing)	83.2 g
Weight per piece (excluding packing)	81.5 g
Customs tariff number	96121010
Country of origin	CN

MM-EMLF (EX24)R C1 WH/BK - Label, highly flexible



0803940

<https://www.phoenixcontact.com/gb/products/0803940>

Technical data

Product properties

Product type	Gerätemarker
Product property	Highly flexible

Marking

Identification technology	Thermal transfer
---------------------------	------------------

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

Foil strength	80 µm
Adhesive	Acrylic
Color	multicolored
	white (RAL 9010)
	black (RAL 9005)
Material	Vinyl polymer
Components	Free from silicone and cadmium

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 75 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	24 months

Dimensions

Height	24 mm
Depth	0.07 mm
Length of roll	8.00 m

Text field

Text field width	8000 mm
Text field height	22 mm

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

MM-EMLF (EX24)R C1 WH/BK - Label, highly flexible



0803940

<https://www.phoenixcontact.com/gb/products/0803940>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/0803940>



cULus Recognized
Approval ID: MH48542

MM-EMLF (EX24)R C1 WH/BK - Label, highly flexible



0803940

<https://www.phoenixcontact.com/gb/products/0803940>

Classifications

ECLASS

ECLASS-13.0	27281103
ECLASS-15.0	27281103

ETIM

ETIM 9.0	EC001288
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

MM-EMLF (EX24)R C1 WH/BK - Label, highly flexible



0803940

<https://www.phoenixcontact.com/gb/products/0803940>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk