



S8VK-S12024

Book type power supply, 120 W, 24VDC, 5A, DIN rail mounting, Push-in terminal, Coated

Specifications

Type	DIN-rail
Mounting method	DIN rail
Phase	Single
Power output	120 W
Efficiency	92 %
Output voltage	24 V
Rated output current	5 A
Power boost ratio	120 %
Temperature range	-40-70 °C
Features	Coated
Terminal type	Push-in
Communication port(s)	None
Alarm function	-
Number of output branches	1
Rated supply voltage at AC 50 Hz	100-240 V
Allowable supply voltage AC	85-264 V
Allowable supply voltage DC	90-350 V
Product Width (unpacked)	55 mm
Product Height (unpacked)	90 mm
Product Depth (unpacked)	90 mm



PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

Related products



S8V-NF
Noise Filter S8V-NF




Electronic Circuit Breaker
S8V-CP - Electronic Circuit Breaker

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



Meet equipment safety requirements by implementing redundant output relays

Flyer

EN PDF 1.33 MB



Panel Building Brochure

EN PDF 3.11 MB



Perfect Power Supply Solutions Brochure

EN PDF 807 KB



S8VK Series Switch Mode Power Supplies Brochure

EN PDF 2.03 MB



S8VK-S Switch Mode Power Supply Datasheet

EN PDF 5.72 MB



S8VK-S/S8FS-G Brochure

EN PDF 2.4 MB



Solution case study No.8 Environment resistance

Brochure

EN PDF 623 KB