



P7SA-14F-ND-PU 24VDC

Socket, DIN rail/surface mounting, 14 pin, push in terminals, for G7SA 6 pole relays, LED indicator

Specifications

Applicable product family	G7SA
Mounting method	DIN rail
Terminal type	Push-in Plus
Product Width (unpacked)	27.7 mm
Product Height (unpacked)	104 mm
Product Depth (unpacked)	65.5 mm
Color	Black
Hold down clip included	✓
Release Lever included	✓
Applicable wire	Solid, Stranded, With ferrules
Applicable ferrules	Round terminals

Accessories



XW5S-P2.5-2RD

Short bar for terminal blocks 2.5 mm² push-in plus models, 2 poles, red color



XW5S-P2.5-4RD

Short bar for terminal blocks 2.5 mm² push-in plus models, 4 poles, red color



XW5S-P2.5-5RD

Short bar for terminal blocks 2.5 mm² push-in plus models, 5 poles, red color

Related products



G7SA

Relays with forcibly guided contacts

Downloads

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



G7SA Relays with Forcibly Guided Contacts Datasheet

EN PDF 3.23 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 29 August, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU