



## PYFZ-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals (standard)

# Specifications

|                           |                        |
|---------------------------|------------------------|
| Applicable product family | G3F, H3YN, MY2, MY2-GS |
| Mounting method           | DIN rail/screw         |
| Terminal type             | Screw                  |
| Product Width (unpacked)  | 23 mm                  |
| Product Height (unpacked) | 31 mm                  |
| Product Depth (unpacked)  | 72 mm                  |
| Color                     | Black                  |
| Hold down clip included   | ✘                      |
| Release Lever included    | ✘                      |
| Applicable ferrules       | Forked terminals       |

## Fits to



### MY2-GS-R AC110/120

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 110/120 VAC



### MY2-GS-R AC12

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 12 VAC



### MY2-GS-R AC220/240

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 220/240 VAC



### MY2-GS-R AC24

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 24 VAC

**MY2-GS-R AC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 48 VAC

**MY2-GS-R DC100/110**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 100/110 VDC

**MY2-GS-R DC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 12 VDC

**MY2-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 24 VDC

**MY2-GS-R DC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical indicator, 48 VDC

**MY2IN-CR-GS-R AC110/120**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 110/120 VAC

**MY2IN-CR-GS-R AC220/240**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 220/240 VAC

**MY2IN-D2-GS-R DC100/110**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button. 100/110 VDC

**MY2IN-D2-GS-R DC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 12 VDC

**MY2IN-D2-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, lockable push test button, 24 VDC

**MY2IN-GS-R AC110/120**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

**MY2IN-GS-R AC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 12 VAC

**MY2IN-GS-R AC220/240**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 220/240 VAC

**MY2IN-GS-R AC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 24 VAC

**MY2IN-GS-R AC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 48 VAC

**MY2IN-GS-R DC100/110**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 100/110 VDC

**MY2IN-GS-R DC12**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 12 VDC

**MY2IN-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 24 VDC

**MY2IN-GS-R DC48**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, lockable push test button, 48 VDC

**MY2K-02 24VDC**

Latching relay, pcb pins, 14-pin, DPDT, 3 A, LED indicator, 24 VDC

**MY2N-D2-GS-R DC24**

Relay, plug-in, 8-pin, DPDT, 10 A, mechanical & LED indicators, Coil Surge Absorption, 24 VDC

**MY2N1-D2 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, reverse coil polarity, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC

**MY2Z 24VDC**

Relay, plug-in, DPDT (bifurcated), 3 A, mechanical indicator, 24 VDC

**MY2ZN 220/240VAC**

Relay, plug-in, DPDT (bifurcated), 3 A, mech. & LED indicator, 220/240 VAC

**MY2ZN 24VDC**

Relay, plug-in, 8-pin, DPDT, bifurcated contacts, 10 A, mech & LED indicators, label facility, 24 VDC

**MY2ZN-D2 24VDC**

Relay, plug-in, 8-pin, DPDT, bifurcated contacts, 10 A, mech & LED indicators, coil suppressor, label facility, 24 VDC

# Accessories



**PFP-100N**

DIN-rail mounting track, 35 x 7.3 mm, 1 m length



**PFP-100N2**

DIN-rail mounting track, 35x16mm, 1m length



**PFP-50N**

Din rail track, 500 mm



**PFP-M**

End plate



**PFP-S**

Spacer



**PYC-A1**

Retaining clips for LY/MY relay & PTF/PYF\_E/N socket



**PYC-E1**

Retaining clips for MY2IN(S) relay & PYF\_A/N socket



**XW5Z-EP12**

Separator Plate for terminal blocks, 12 mm width



**XW5Z-EP6**

End bracket for terminal blocks, 6 mm width



**Y92H-3**

Clips for H3Y(N) timer & PYF socket

CAD Library



## EAC Mark removal Discontinuation Notice

EN PDF 221 KB



## MY(S) Miniature Power Relays Datasheet

EN PDF 9.24 MB